



# GreenUp Highbay

## BY550X LED200/NW ACW2 IS HRO

LED module 20600 lm, Neutral white, High-rack optic

GreenUp Highbay BY550 is a high efficient and reliable LED highbay for industrial high-ceiling facilities without humid and dusty requirement, designed for both new project and retrofit. This lighting system can deliver up to 88% energy savings with the integrated G2 Acticlume Wireless. It delivers point to point replace up to 400W HID and T5 6x54W highbay with easy installation. There are three beam shapes to choose with good light quality CRI85 and UGR 17. Integrated with G2 Acticlume Wireless, GreenUp BY550 provide connected lighting with daylight , occupancy sensor, and ZigBee wireless communication, will increase your savings by upgrading to an intelligent system and delivering one-stop solution for your Factory, Warehouse, Distribution center, Indoor spot hall, and other high ceiling indoor application.

### Product data

General Information			
Lamp family code	LED206 [LED module 20600 lm]	Correlated Color Temperature (Nom)	4000 K
Light source replaceable	No	Luminous Efficacy (rated) (Nom)	100 lm/W
Number of gear units	2 units	Color rendering index (CRI)	>85
Gear	-	Light source color	Neutral white
Driver included	Yes	Optic type	High-rack optic
Light source engine type	LED	Optical cover type	Polycarbonate bowl/cover clear
Glow-wire test	Temperature 650 °C, duration 30 s	Luminaire light beam spread	90°
Flammability mark	-	Operating and Electrical	
CE mark	CE mark	Input Voltage	220 to 240 V
ENEC mark	-	Line Frequency	50 to 60 Hz
Light Technical		Power Consumption	160 W
Luminous Flux	14,000 lm	Power Factor (Fraction)	0.9
		Connection	Screw connection block 3-pole

## GreenUp Highbay

Cable	-
Number of products on MCB of 16 A type B	12
<b>Temperature</b>	
Ambient temperature range	-20 to +40 °C
<b>Controls and Dimming</b>	
Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Control interface	-
Constant light output	Yes
<b>Mechanical and Housing</b>	
Housing Material	Metal – Plastic
Optic material	Polymethyl methacrylate
Optical cover material	Polymethyl methacrylate
Housing Color	White
Optical cover finish	Clear
<b>Approval and Application</b>	
Ingress protection code	IP20 [Finger-protected]

Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class I
<b>Initial Performance (IEC Compliant)</b>	
Luminous flux tolerance	+/-7.5%
Initial chromaticity	-
Power consumption tolerance	+/-10%
<b>Application Conditions</b>	
Maximum dim level	1% (depends on dimmer, ELV)
<b>Product Data</b>	
Order product name	BY550X LED200/NW ACW2 IS HRO
Full product name	BY550X LED200/NW ACW2 IS HRO
Full product code	911401537121
Order code	911401537121
Material Nr. (12NC)	911401537121
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

### Dimensional drawing

