



GreenUp Highbay

BY550X LED200/CW ACW2 IS HRO

LED module 20600 lm, Cool white, High-rack optic

GreenUp Highbay BY550 is a high efficient and reliable LED highbay for industrial high-ceiling facilities without humid and dusty requirement, designed for both new project and retrofit. This lighting system can deliver up to 88% energy savings with the integrated G2 Actimlume Wireless. It delivers point to point replace up to 400W HID and T5 6x54W higbay with easy installation. There are three beam shapes to choose with good light quality CRI85 and UGR 17. Integrated with G2 Actilume Wireless, GreenUp BY550 provide connected lighting with daylight , occupancy sensor, and ZigBee wireless communication, will increase your savings by upgrading to an intelligent system and delivering one-stop solution for your Factory, Warehouse, Distribution center, Indoor spot hall, and other high ceiling indoor application.

Product data

General Information			
Lamp family code	LED206 [LED module 20600 lm]	Light source color	Cool white
Light source replaceable	No	Optic type	High-rack optic
Number of gear units	2 units	Optical cover type	Polycarbonate bowl/cover clear
Gear	-	Luminaire light beam spread	90°
Driver included	Yes	Operating and Electrical	
CE mark	CE mark	Input Voltage	220-240 V
Flammability mark	-	Line Frequency	50 to 60 Hz
ENEC mark	-	Power Consumption	160 W
Glow-wire test	Temperature 650 °C, duration 30 s	Power Factor (Fraction)	0.9
Light Technical		Connection	Screw connection block 3-pole
Correlated Color Temperature (Nom)	6500 K	Cable	-
Color rendering index (CRI)	>85		

GreenUp Highbay

Temperature

Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Constant light output	Yes

Mechanical and Housing

Housing Material	Metal–Plastic
Optic material	Polymethyl methacrylate
Housing Color	White

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7.5%
Initial chromaticity	-
Power consumption tolerance	+/-10%

Application Conditions

Maximum dim level	1% (depends on dimmer, ELV)
-------------------	-----------------------------

Product Data

Order product name	BY550X LED200/CW ACW2 IS HRO
Full product name	BY550X LED200/CW ACW2 IS HRO
Full product code	911401537621
Order code	911401537621
Material Nr. (12NC)	911401537621
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

