



# GreenUp Highbay

## BY550X LED100/CW ACW2 IS WB

LED module 10500 lm, Cool white, Wide beam

GreenUp Highbay BY550 is a high efficient and reliable LED highbay for industrial high-ceiling facilities without humid and dusty requirement, designed for both new project and retrofit. This lighting system can deliver up to 88% energy savings with the integrated G2 Acticlume Wireless. It delivers point to point replace up to 400W HID and T5 6x54W highbay with easy installation. There are three beam shapes to choose with good light quality CRI85 and UGR 17. Integrated with G2 Acticlume Wireless, GreenUp BY550 provide connected lighting with daylight , occupancy sensor, and ZigBee wireless communication, will increase your savings by upgrading to an intelligent system and delivering one-stop solution for your Factory, Warehouse, Distribution center, Indoor spot hall, and other high ceiling indoor application.

### Product data

General Information		Light source color	
Lamp family code	LED105 [LED module 10500 lm]	Light source color	Cool white
Light source replaceable	No	Optic type	Wide beam
Number of gear units	1 unit	Optical cover type	Polycarbonate bowl/cover clear
Gear	-	Luminaire light beam spread	90°
Driver included	Yes	Operating and Electrical	
CE mark	CE mark	Input Voltage	220-240 V
Flammability mark	-	Line Frequency	50 to 60 Hz
ENEC mark	-	Power Consumption	80 W
Glow-wire test	Temperature 650 °C, duration 30 s	Power Factor (Fraction)	0.9
Light Technical		Connection	Screw connection block 3-pole
Correlated Color Temperature (Nom)	6500 K	Cable	-
Color rendering index (CRI)	>85		

# GreenUp Highway

## Temperature

Ambient temperature range	-20 to +40 °C
---------------------------	---------------

## Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Constant light output	Yes

## Mechanical and Housing

Housing Material	Metal-Plastic
Optic material	Polymethyl methacrylate
Housing Color	White

## Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class I

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7.5%
Initial chromaticity	-
Power consumption tolerance	+/-10%

## Application Conditions

Maximum dim level	1% (depends on dimmer, ELV)
-------------------	-----------------------------

## Product Data

Order product name	BY550X LED100/CW ACW2 IS WB
Full product name	BY550X LED100/CW ACW2 IS WB
Full product code	911401538721
Order code	911401538721
Material Nr. (12NC)	911401538721
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

## Dimensional drawing

