



GreenSpace Downlight G4

DN291B 1xDLED-4000 PSU WH

GreenSpace Downlight G4, 11.6 W, 1000 lm, 4000 K, Beam angle 60 to 120°, Matte, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

General Information		
Light source replaceable	No	
Number of gear units	1 unit	
Light source engine type	LED	
CE mark	CE mark	
ENEC mark	-	
Glow-wire test	Temperature 650 °C, duration 30 s	
Light Technical		
Luminous Flux	1,000 lm	
Correlated Color Temperature (Nom)	4000 K	
Luminous Efficacy (rated) (Nom)	89 lm/W	
Color rendering index (CRI)	>80	
Number of light sources	1	
Light source color	840 neutral white	
Optic type	Beam angle 60 to 120°	
Optical cover type	Transparent bowl with white cover	

Luminaire light beam spread	90°	
Operating and Electrical		
Input Voltage	220-240 V	
Line Frequency	50 or 60 Hz	
Power Consumption	11.6 W	
Power Factor (Fraction)	0.9	
Number of products on MCB of 16 A type B	30	
Temperature		
Ambient temperature range	-20 to +40 °C	
Controls and Dimming		
Dimmable	No	
Driver/power unit/transformer	Power supply unit (On/Off)	
Control interface	-	

Datasheet, 2023, April 29 data subject to change


GreenSpace Downlight G4


Aluminum	
Polycarbonato	
Polycarbonate	
Polycarbonate	
Polycarbonate	
White	
Matte	
IP20 [Finger-protected]	
IKO2 [0.2 J standard]	
Safety class I	

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%	
Power consumption tolerance	+/-10%	
Product Data		
Order product name	DN291B 1xDLED-4000 PSU WH	
Full product name	DN291B 1xDLED-4000 PSU WH	
Full product code	911401565021	
Order code	911401565021	
Material Nr. (12NC)	911401565021	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	24	

Dimensional drawing

Dimension 灯具尺寸	A (mm)	B (mm)
DN290B IxDLED / ALU	95 / 99	Ф 122
DN291B 1xDLED / ALU	105 /109	Ф 167
DN292B 1xDLED / ALU	114 / 118	Ф 218
DN293B IxDLED / ALU	114 / 118	Ф 218





Dimension 灯具尺寸	A (mm)	B (mm)
DN290B IxDLED / ALU	95 / 99	Ф 122
DN291B 1xDLED / ALU	105 /109	Ф 167
DN292B 1xDLED / ALU	114 / 118	Ф 218
DN293B 1xDLED / ALU	114 / 118	Ф 218

