



GreenSpace Downlight G4

DN291B 1xDLED-4000 PSD ALU

GreenSpace Downlight G4, 11.6 W, 4000 K, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

| | | | |
|------------------------------------|-----------------------------------|---------------------------------------|--|
| General Information | | Power Consumption | |
| Light source replaceable | No | 11.6 W | |
| Number of gear units | 1 unit | Power Factor (Fraction) | |
| CE mark | CE mark | 0.9 | |
| ENEC mark | - | Temperature | |
| Glow-wire test | Temperature 650 °C, duration 30 s | Ambient temperature range | |
| Light Technical | | -20 to +40 °C | |
| Correlated Color Temperature (Nom) | 4000 K | Controls and Dimming | |
| Number of light sources | 1 | Driver/power unit/transformer | |
| Light source color | 840 neutral white | Power supply unit with DALI interface | |
| Optic type | Beam angle 60 to 120° | Constant light output | |
| Optical cover type | Transparent bowl with white cover | No | |
| Luminaire light beam spread | 90° | Mechanical and Housing | |
| Operating and Electrical | | Housing Material | |
| Input Voltage | 220-240 V | Aluminum | |
| | | Reflector material | |
| | | Polycarbonate | |
| | | Optic material | |
| | | Polycarbonate | |
| | | Approval and Application | |
| | | Ingress protection code | |
| | | IP20 [Finger-protected] | |

GreenSpace Downlight G4

| | |
|-------------------------------------|----------------------------|
| Mech. impact protection code | IK02 [0.2 J standard] |
| Initial Performance (IEC Compliant) | |
| Luminous flux tolerance | +/-10% |
| Power consumption tolerance | +/-10% |
| Product Data | |
| Order product name | DN291B 1xDLED-4000 PSD ALU |

| | |
|---------------------------------|----------------------------|
| Full product name | DN291B 1xDLED-4000 PSD ALU |
| Full product code | 911401565321 |
| Order code | 01565321 |
| Material Nr. (12NC) | 911401565321 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 24 |

Dimensional drawing

