



# GreenSpace Downlight G4

## DN291B 1xDLED-6500 PSD ALU

GreenSpace Downlight G4, 11.6 W, 6500 K, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

### Product data

<b>General Information</b>		<b>Power Consumption</b>		11.6 W
Light source replaceable	No	<b>Power Factor (Fraction)</b>		0.9
Number of gear units	1 unit	<b>Temperature</b>		
CE mark	CE mark	<b>Ambient temperature range</b>		-20 to +40 °C
ENEC mark	-	<b>Controls and Dimming</b>		
Glow-wire test	Temperature 650 °C, duration 30 s	<b>Driver/power unit/transformer</b>		Power supply unit with DALI interface
<b>Light Technical</b>		<b>Constant light output</b>		No
Correlated Color Temperature (Nom)	6500 K	<b>Mechanical and Housing</b>		
Number of light sources	1	<b>Housing Material</b>		Aluminum
Light source color	865 cool daylight	<b>Reflector material</b>		Polycarbonate
Optic type	Beam angle 60 to 120°	<b>Optic material</b>		Polycarbonate
Optical cover type	Transparent bowl with white cover	<b>Approval and Application</b>		
Luminaire light beam spread	90°	<b>Ingress protection code</b>		IP20 [Finger-protected]
<b>Operating and Electrical</b>				
Input Voltage	220-240 V			

GreenSpace Downlight G4

Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Full product code	911401565421

Order product name	DN291B 1xDLED-6500 PSD ALU
Order code	911401565421
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	911401565421
Full product name	DN291B 1xDLED-6500 PSD ALU

Dimensional drawing

