



GreenSpace Downlight G4

DN292B 1xDLED-3000 PSD ALU

GreenSpace Downlight G4, 16 W, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

General Information	
Light source replaceable	No
Number of gear units	1 unit
CE mark	CE mark
ENEC mark	-
Glow-wire test	Temperature 650 °C, duration 30 s
Light Technical	
Number of light sources	1
Light source color	830 warm white
Optic type	Beam angle 60 to 120°
Optical cover type	Transparent bowl with white cover
Luminaire light beam spread	90°
Operating and Electrical	
Input Voltage	220-240 V
Power Consumption	16 W

Power Factor (Fraction)		0.9
Temperature		
Ambient temperature range	-20 to +40 °C	
Controls and Dimming		
Driver/power unit/transformer	Power supply unit with DALI interface	
Constant light output	No	
Mechanical and Housing		
Housing Material	Aluminum	
Reflector material	Polycarbonate	
Optic material	Polycarbonate	
Approval and Application		
Ingress protection code	IP20 [Finger-protected]	

GreenSpace Downlight G4

Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Full product code	911401566421

Order product name	DN292B 1xDLED-3000 PSD ALU
Order code	911401566421
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401566421
Full product name	DN292B 1xDLED-3000 PSD ALU

Dimensional drawing

