



GreenSpace Downlight G4

DN292B 1xDLED-6500 PSD WH

GreenSpace Downlight G4, 16 W, 6500 K, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

General Information		Power Consumption		16 W
Light source replaceable	No	Power Factor (Fraction)		0.9
Number of gear units	1 unit	Temperature		
CE mark	CE mark	Ambient temperature range		-20 to +40 °C
ENEC mark	-	Controls and Dimming		
Glow-wire test	Temperature 650 °C, duration 30 s	Driver/power unit/transformer		Power supply unit with DALI interface
Light Technical		Constant light output		No
Correlated Color Temperature (Nom)	6500 K	Mechanical and Housing		
Number of light sources	1	Housing Material		Aluminum
Light source color	865 cool daylight	Reflector material		Polycarbonate
Optic type	Beam angle 60 to 120°	Optic material		Polycarbonate
Optical cover type	Transparent bowl with white cover	Approval and Application		
Luminaire light beam spread	90°	Ingress protection code		IP20 [Finger-protected]
Operating and Electrical				
Input Voltage	220-240 V			

GreenSpace Downlight G4

Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	DN292B 1xDLED-6500 PSD WH

Full product name	DN292B 1xDLED-6500 PSD WH
Full product code	911401566921
Order code	911401566921
Material Nr. (12NC)	911401566921
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

Dimensional drawing

