



GreenSpace Downlight G4

DN293B 1xDLED-4000 PSD ALU

GreenSpace Downlight G4, 22 W, 4000 K, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

General Information		Power Consumption	
Light source replaceable	No	22 W	
Number of gear units	1 unit	Power Factor (Fraction)	
CE mark	CE mark	0.9	
ENEC mark	-	Temperature	
Glow-wire test	Temperature 650 °C, duration 30 s	Ambient temperature range	
Light Technical		-20 to +40 °C	
Correlated Color Temperature (Nom)		Controls and Dimming	
4000 K		Driver/power unit/transformer	
Number of light sources		Power supply unit with DALI interface	
1		Constant light output	
Light source color		No	
840 neutral white		Mechanical and Housing	
Optic type		Housing Material	
Beam angle 60 to 120°		Aluminum	
Optical cover type		Reflector material	
Transparent bowl with white cover		Polycarbonate	
Luminaire light beam spread		Optic material	
90°		Polycarbonate	
Operating and Electrical		Approval and Application	
Input Voltage		Ingress protection code	
220-240 V		IP20 [Finger-protected]	

GreenSpace Downlight G4

Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	DN293B 1xDLED-4000 PSD ALU

Full product name	DN293B 1xDLED-4000 PSD ALU
Full product code	911401567721
Order code	911401567721
Material Nr. (12NC)	911401567721
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

Dimensional drawing

