



GreenSpace Downlight G4

DN293B 1xDLED-3000 PSD ALU CAU

GreenSpace Downlight G4, 22 W, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

General Information		Power Factor (Fraction)		0.9
Light source replaceable	No	Cable	Cord with plug SAA 3-pole	
Number of gear units	1 unit	Temperature		
CE mark	CE mark	Ambient temperature range	-20 to +40 °C	
ENEC mark	-	Controls and Dimming		
Glow-wire test	Temperature 650 °C, duration 30 s	Driver/power unit/transformer	Power supply unit with DALI interface	
Light Technical		Constant light output	No	
Number of light sources	1	Mechanical and Housing		
Light source color	830 warm white	Housing Material	Aluminum	
Optic type	Beam angle 60 to 120°	Reflector material	Polycarbonate	
Optical cover type	Transparent bowl with white cover	Optic material	Polycarbonate	
Luminaire light beam spread	90°	Approval and Application		
Operating and Electrical		Ingress protection code	IP20 [Finger-protected]	
Input Voltage	220-240 V			
Power Consumption	22 W			

GreenSpace Downlight G4

Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	DN293B 1xDLED-3000 PSD ALU CAU
Full product name	DN293B 1xDLED-3000 PSD ALU CAU

Full product code	871016330051199
Order code	911401569421
Material Nr. (12NC)	911401569421
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163300511
Numerator - Packs per outer box	12

Dimensional drawing

