



# GreenSpace G5

## DN393B LED22/840 POE D200 WH GC

GreenSpace G5, 20.5 W, 2200 lm, 4000 K, Power over Ethernet, High-gloss high reflectance, Matte, Finger-protected

GreenSpace Gen5 is a new LED downlight range combining light efficiency and comfort with product diversity and system compatibility

### Product data

<b>General Information</b>		<b>Luminaire light beam spread</b>	
Light source replaceable	No	80°	
Number of gear units	1 unit	<b>Operating and Electrical</b>	
Driver included	Yes	<b>Input Voltage</b>	
Light source engine type	LED	53 V	
CE mark	-	<b>Line Frequency</b>	
Warranty period	3 years	~ Hz	
Flammability mark	For mounting on normally flammable surfaces	<b>Power Consumption</b>	
Glow-wire test	Temperature 650 °C, duration 30 s	20.5 W	
<b>Light Technical</b>		<b>Power Factor (Fraction)</b>	
Luminous Flux	2,200 lm	1	
Correlated Color Temperature (Nom)	4000 K	<b>Number of products on MCB of 16 A type B -</b>	
Luminous Efficacy (rated) (Nom)	107 lm/W		
Color rendering index (CRI)	>80	<b>Temperature</b>	
Beam angle of light source	92 degree(s)	<b>Ambient temperature range</b>	
Light source color	840 neutral white	0 to +40 °C	
Optic type	High-gloss high reflectance	<b>Controls and Dimming</b>	
Optical cover type	Transparent bowl with white cover	<b>Dimmable</b>	
		Yes	
		<b>Driver/power unit/transformer</b>	
		Luminaire controller with power over Ethernet	
		<b>Control interface</b>	
		Power over Ethernet	
		<b>Constant light output</b>	
		No	
		<b>Mechanical and Housing</b>	
		<b>Housing Material</b>	
		Aluminum die cast	

GreenSpace G5

Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	Black and white
Optical cover finish	Matte
Overall length	0 mm
Overall width	0 mm
Overall height	108 mm
Overall diameter	216 mm
Dimensions (Height x Width x Depth)	108 x 0 x 0 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class III

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38,0.38) SDCM<5

Power consumption tolerance	+/-10%
-----------------------------	--------

Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	0.12 %
Median useful life L70B50	50,000 hour(s)
Median useful life L80B50	43,000 hour(s)
Median useful life L90B50	20,000 hour(s)

Product Data

Order product name	DN393B LED22/840 POE D200 WH GC
Full product name	DN393B LED22/840 POE D200 WH GC
Full product code	911401576241
Order code	911401576241
Material Nr. (12NC)	911401576241
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

