



# GreenSpace Downlight G4

## DN293B 1xDLED-6500 PSU ALU WP

GreenSpace Downlight G4, 22 W, 6500 K, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

#### **Product data**

The state of the s		
General Information		
Light source replaceable	No	
Number of gear units	1 unit	
CE mark	CE mark	
ENEC mark	-	
Glow-wire test	Temperature 650 °C, duration 30 s	
Light Technical		
Correlated Color Temperature (Nom)	6500 K	
Number of light sources	1	
Light source color	865 cool daylight	
Optic type	Beam angle 60 to 120°	
Optical cover type	Transparent bowl with white cover	
Luminaire light beam spread	90°	
Operating and Electrical		
Input Voltage	220-240 V	

Power Consumption	22 W	
Power Factor (Fraction)	0.9	
Temperature		
Ambient temperature range	-20 to +40 °C	
Controls and Dimming		
Dimmable	No	
Driver/power unit/transformer	Power supply unit (On/Off)	
Constant light output	Yes	
Mechanical and Housing		
Housing Material	Aluminum	
Reflector material	Polycarbonate	
Optic material	Polycarbonate	

Datasheet, 2023, April 29 data subject to change


# **GreenSpace Downlight G4**


Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IKO2 [0.2 J standard]
Initial Performance (IEC Complian	nt)
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	DN293B 1xDLED-6500 PSU ALU WP

Full product name	DN293B 1xDLED-6500 PSU ALU WP	
Full product code	911401580121	
Order code	911401580121	
Material Nr. (12NC)	911401580121	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	12	

## Dimensional drawing

Dimension 灯具尺寸	A (mm)	B (mm)
DN290B IxDLED / ALU	95 / 99	Ф 122
DN291B 1xDLED / ALU	105 /109	Ф 167
DN292B 1xDLED / ALU	114 / 118	Ф 218
DN293B IxDLED / ALU	114 / 118	Ф 218





Dimension 灯具尺寸	A (mm)	B (mm)	
DN290B IxDLED / ALU	95 / 99	Ф 122	
DN291B 1xDLED / ALU	105 /109	Ф 167	
DN292B IxDLED / ALU	114/118	Ф 218	
DN293B IxDLED / ALU	114 / 118	Ф 218	

