



# GreenSpace Downlight G4

## DN293B 1xDLED-4000 PSU WH CAU

GreenSpace Downlight G4, 22 W, 4000 K, Beam angle 60 to 120°, Finger-protected

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

#### **Product data**

General Information	
Light source replaceable	No
Number of gear units	1 unit
CE mark	CE mark
ENEC mark	-
Glow-wire test	Temperature 650 °C, duration 30 s
Light Technical	
Correlated Color Temperature (Nom)	4000 K
Number of light sources	1
Light source color	840 neutral white
Optic type	Beam angle 60 to 120°
Optical cover type	Transparent bowl with white cover
Luminaire light beam spread	90°
Operating and Electrical	
Input Voltage	220-240 V

Power Consumption	22 W
Power Factor (Fraction)	0.9
Cable	Cord with plug SAA 3-pole
Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	Yes
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	Polycarbonate
Optic material	Polycarbonate

### GreenSpace Downlight G4

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	DN293B 1xDLED-4000 PSU WH CAU

Full product name	DN293B 1xDLED-4000 PSU WH CAU	
Full product code	871016330060399	
Order code	911401581321	
Material Nr. (12NC)	911401581321	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8710163300603	
Numerator - Packs per outer box	12	

#### **Dimensional drawing**





Dimension 灯具尺寸	A (mm)	B (mm)
DN290B IxDLED / ALU	95 / 99	Φ 122
DN291B 1xDLED / ALU	105 /109	Φ 167
DN292B IxDLED / ALU	114/118	Φ218
DN293B IxDLED / ALU	4/  8	Φ218
Mir Unit	- 500mm	Min.200mm





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, August 2 - data subject to change