



GreenSpace G5

DN393B LED22/840 PSU D200 WH WP CAU

GreenSpace G5, 19 W, 2200 lm, 4000 K, High-gloss high reflectance, Matte, Finger-protected; dust accumulation-protected, splash-proof

GreenSpace Gen5 is a new LED downlight range combining light efficiency and comfort with product diversity and system compatibility

Product data

| General Information | | Luminaire light beam spread | |
|------------------------------------|---|---|--------------------------|
| Light source replaceable | No | 80° | |
| Number of gear units | 1 unit | Operating and Electrical | |
| Driver included | Yes | Input Voltage | 220-240 V |
| Light source engine type | LED | Line Frequency | 50 or 60 Hz |
| CE mark | CE mark | Inrush current | 2.2 A |
| Warranty period | 3 years | Inrush time | 0.045 ms |
| Flammability mark | For mounting on normally flammable surfaces | Power Consumption | 19 W |
| Glow-wire test | Temperature 650 °C, duration 30 s | Power Factor (Fraction) | 0.95 |
| Light Technical | | Connection | Push-in connector 6-pole |
| Luminous Flux | 2,200 lm | Cable | Cable with plug |
| Correlated Color Temperature (Nom) | 4000 K | Number of products on MCB of 16 A type B 48 | |
| Luminous Efficacy (rated) (Nom) | 116 lm/W | Temperature | |
| Color rendering index (CRI) | >80 | Ambient temperature range | -20 to +40 °C |
| Beam angle of light source | 92 degree(s) | Controls and Dimming | |
| Light source color | 840 neutral white | Dimmable | No |
| Optic type | High-gloss high reflectance | Control interface | - |
| Optical cover type | Transparent bowl with white cover | | |

| | |
|-----------------------|----|
| Constant light output | No |
|-----------------------|----|

Mechanical and Housing

| | |
|-------------------------------------|-------------------|
| Housing Material | Aluminum die cast |
| Reflector material | Polycarbonate |
| Optic material | Polycarbonate |
| Optical cover material | Polycarbonate |
| Housing Color | Black and white |
| Optical cover finish | Matte |
| Overall length | 0 mm |
| Overall width | 0 mm |
| Overall height | 108 mm |
| Overall diameter | 216 mm |
| Dimensions (Height x Width x Depth) | 108 x 0 x 0 mm |

Approval and Application

| | |
|------------------------------|---|
| Ingress protection code | IP20/54 [Finger-protected; dust accumulation-protected, splash-proof] |
| Mech. impact protection code | IK02 [0.2 J standard] |
| Protection class IEC | Safety class I |

Initial Performance (IEC Compliant)

| | |
|-----------------------------|--------------------|
| Luminous flux tolerance | +/-10% |
| Initial chromaticity | (0.38,0.38) SDCM<5 |
| Power consumption tolerance | +/-10% |

Over Time Performance (IEC Compliant)

| | |
|-------------------------------|----------------|
| Driver failure rate at 5000 h | 0.12 % |
| Median useful life L70B50 | 50,000 hour(s) |
| Median useful life L80B50 | 43,000 hour(s) |
| Median useful life L90B50 | 20,000 hour(s) |

Application Conditions

| | |
|-------------------|----------------|
| Maximum dim level | Not applicable |
|-------------------|----------------|

Product Data

| | |
|---------------------------------|-------------------------------------|
| Order product name | DN393B LED22/840 PSU D200 WH WP CAU |
| Full product name | DN393B LED22/840 PSU D200 WH WP CAU |
| Full product code | 871016334949700 |
| Order code | 911401584141 |
| Material Nr. (12NC) | 911401584141 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8710163349497 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 8710163349497 |

Dimensional drawing



