



SmartPanel 2.0

RC160V LED34S/865 PSU W60L60

SmartPanel 2.0, 865 cool daylight

SmartPanel 2.0 keeps the design continuity of SmartPanel 1.1 with performance improvement and more cost effective structure. It offers two lumen options with higher system efficacy, 80lm/W @ 4000K. Reliability is improved by the extending of lifetime from 30K hours to 50K hours L70 Ta 25°C

Product data

General Information		Power Factor (Fraction)		0.9
Light source replaceable	No			
Number of gear units	1 unit	Temperature		
Driver included	No	Ambient temperature range		-20 to +40 °C
CE mark	CE mark			
ENEC mark	-	Controls and Dimming		
Glow-wire test	Temperature 650 °C, duration 30 s	Dimmable		No
		Driver/power unit/transformer		Power supply unit (On/Off)
		Constant light output		Yes
Light Technical				
Correlated Color Temperature (Nom)	6500 K	Mechanical and Housing		
Color rendering index (CRI)	80	Housing Material		Steel
Light source color	865 cool daylight	Optic material		Polymethyl methacrylate
Optic type	Beam angle 60 to 120°	Housing Color		White
Optical cover type	Transparent bowl with white cover			
Luminaire light beam spread	120°	Approval and Application		
		Ingress protection code		IP20 [Finger-protected]
		Mech. impact protection code		IK02 [0.2 J standard]
Operating and Electrical				
Input Voltage	220-240 V			
Power Consumption	42 W			

SmartPanel 2.0

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	RC160V LED34S/865 PSU W60L60
Full product name	RC160V LED34S/865 PSU W60L60

Full product code	911401599811
Order code	911401599811
Material Nr. (12NC)	911401599811
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

