
PHILIPS Lighting



Tango G2 LED

BVP283 LED293/WW 315W 220-240V AWBE

Tango G2 LED, 29300 lm, 315 W, 740 neutral white, Safety class L

Tango G2 LED is a general purpose LED flood lighting luminiare for various lighting applications, such as area lighting, bill-board, façade, industry area, recreational sports and other general applications. The Tango G2 LED flood light incorporates LED light source, optical system, heat sink and driver into one compact housing. Its specially designed heat sink incorporates aesthetics and functionality to ensure reliability and long lifetime. Tango G2 LED takes advantage of LED technology which provides energy savings and a longer lifetime, bringing area lighting into a new era.

Product data

| General Information | |
|------------------------------------|-------------------|
| Driver included | Yes |
| Lighting Technology | LED |
| CE mark | CE mark |
| | |
| Light Technical | |
| Luminous Flux | 29,300 lm |
| Correlated Color Temperature (Nom) | 3000 K |
| Luminous Efficacy (rated) (Nom) | 90 lm/W |
| Color rendering index (CRI) | >70 |
| Light source color | 740 neutral white |
| Optical cover type | Glass |
| | |
| Operating and Electrical | |
| Input Voltage | 220-240 V |
| Line Frequency | 50 to 60 Hz |
| Line Frequency | 50 to 60 Hz |
| | |


| Power Consumption | 315 W |
|---------------------------|--------------------------|
| Power Factor (Fraction) | 0.95 |
| Connection | Flying leads/wires |
| Cable | Cable 1.5 m without plug |
| | |
| Temperature | |
| Ambient temperature range | -40 to +50 °C |
| | |
| Controls and Dimming | |
| Dimmable | No |
| Control interface | - |
| | |
| Mechanical and Housing | |
| Housing Material | Aluminum die cast |
| Optic material | Polycarbonate |
| Optical cover material | Polycarbonate |
| | |

Tango G2 LED

| Housing Color | Aluminum and gray |
|-------------------------------------|--|
| Overall length | 480 mm |
| Overall width | 655 mm |
| Overall height | 60 mm |
| Dimensions (Height x Width x Depth) | 60 x 655 x 480 mm |
| | |
| Approval and Application | |
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK07 [2 J reinforced] |
| Protection class IEC | Safety class I |
| | |
| Initial Performance (IEC Compliant) | |
| Luminous flux tolerance | +/-10% |

Power consumption tolerance +/-10% **Product Data** Order product name BVP283 LED293/WW 315W 220-240V AWBE Full product name BVP283 LED293/WW 315W 220-240V AWBE Full product code 911401605003 Order code 911401605003 Material Nr. (12NC) 911401605003 Numerator - Quantity Per Pack 1 Numerator - Packs per outer box 1

Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 16 - data subject to change