



UNIstrip G2 RGB

BCP280 G2 9xLED-HP/RGB 24V L313 WB

UNIstrip G2 RGB, 570 lm, 13 W, Red, green and blue, Wide beam angle 50°, Dynamix DMX, Safety class III, Mounting bracket adjustable

UNIstrip G2 is a LED lighting fixture designed for wide range architecture wall washer lighting applications. UNIstrip G2 offers reliable quality and outstanding performance

Product data

| General Information | | | |
|------------------------------------|---|-------------------------------|--------------------------|
| Light source replaceable | No | Optical cover type | Polycarbonate small |
| Number of gear units | 1 unit | Optic type outdoor | Wide beam angle 50° |
| Driver included | No | Operating and Electrical | |
| Light source engine type | LED | Input Voltage | 24 DC V |
| Lighting Technology | LED | Power Consumption | 13 W |
| CE mark | CE mark | Power Factor (Fraction) | 0.95 |
| Warranty period | 3 years | Connection | Flying leads/wires |
| Flammability mark | For mounting on normally flammable surfaces | Cable | Cable 1.5 m without plug |
| ENEC mark | - | Temperature | |
| EU RoHS compliant | Yes | Ambient temperature range | -40 to +50 °C |
| Light Technical | | Controls and Dimming | |
| Luminous Flux | 570 lm | Dimmable | Yes |
| Standard tilt angle posttop | - | Driver/power unit/transformer | Electronic transformer |
| Standard tilt angle side entry | - | Control interface | Dynamix DMX |
| Correlated Color Temperature (Nom) | - | Constant light output | No |
| Luminous Efficacy (rated) (Nom) | 44 lm/W | | |
| Color rendering index (CRI) | - | | |
| Light source color | Red, green and blue | | |

UNIstrip G2 RGB

| Mechanical and Housing | |
|-------------------------------------|--|
| Housing Material | Aluminum extruded |
| Optic material | Polycarbonate |
| Optical cover material | Polycarbonate |
| Fixation material | Aluminum |
| Housing Color | Aluminum and black |
| Mounting device | Mounting bracket adjustable |
| Optical cover shape | Flat |
| Optical cover finish | Clear |
| Overall length | 313 mm |
| Overall width | 63 mm |
| Overall height | 59 mm |
| Dimensions (Height x Width x Depth) | 59 x 63 x 313 mm |
| Approval and Application | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |
| Protection class IEC | Safety class III |

| Initial Performance (IEC Compliant) | |
|-------------------------------------|------------------------------------|
| Luminous flux tolerance | +/-10% |
| Power consumption tolerance | +/-15% |
| Application Conditions | |
| Maximum dim level | 0% (digital) |
| Product Data | |
| Order product name | BCP280 G2 9xLED-HP/RGB 24V L313 WB |
| Full product name | BCP280 G2 9xLED-HP/RGB 24V L313 WB |
| Full product code | 911401621103 |
| Order code | 911401621103 |
| Material Nr. (12NC) | 911401621103 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 8 |

Dimensional drawing

