



UNIstrip G2 RGB

BCP280 G2 36xLED-HP/RGB 24V L1190 WB

UNIstrip G2 RGB, 2280 lm, 51 W, Red, green and blue, Wide beam angle 50°, Dynamix DMX, Safety class III, Mounting bracket adjustable

UNIstrip G2 is a LED lighting fixture designed for wide range architecture wall washer lighting applications. UNIstrip G2 offers reliable quality and outstanding performance

Product data

General Information			
Light source replaceable	No	Optical cover type	Polycarbonate small
Number of gear units	1 unit	Optic type outdoor	Wide beam angle 50°
Driver included	No	Operating and Electrical	
Light source engine type	LED	Input Voltage	24 DC V
Lighting Technology	LED	Power Consumption	51 W
CE mark	CE mark	Power Factor (Fraction)	0.95
Warranty period	3 years	Connection	Flying leads/wires
Flammability mark	For mounting on normally flammable surfaces	Cable	Cable 1.5 m without plug
ENEC mark	-	Temperature	
EU RoHS compliant	Yes	Ambient temperature range	-40 to +50 °C
Light Technical		Controls and Dimming	
Luminous Flux	2,280 lm	Dimmable	Yes
Standard tilt angle posttop	-	Driver/power unit/transformer	Electronic transformer
Standard tilt angle side entry	-	Control interface	Dynamix DMX
Correlated Color Temperature (Nom)	-	Constant light output	No
Luminous Efficacy (rated) (Nom)	45 lm/W		
Color rendering index (CRI)	-		
Light source color	Red, green and blue		

UNIstrip G2 RGB

Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Aluminum and black
Mounting device	Mounting bracket adjustable
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	1,190 mm
Overall width	63 mm
Overall height	59 mm
Dimensions (Height x Width x Depth)	59 x 63 x 1190 mm
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class III

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-15%
Application Conditions	
Maximum dim level	0% (digital)
Product Data	
Order product name	BCP280 G2 36xLED-HP/RGB 24V L1190 WB
Full product name	BCP280 G2 36xLED-HP/RGB 24V L1190 WB
Full product code	911401621403
Order code	911401621403
Material Nr. (12NC)	911401621403
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

Dimensional drawing

