



UNIstrip G3

BCP280 G3 5LEDHP/4000 L300 24V A

UNIstrip G3, 1000 lm, 9.6 W, Neutral white, Safety class III, Mounting bracket adjustable

UNI strip G3 is a LED wall washer lighting fixture designed for architectural lighting applications. UNIstrip G3 offers reliable quality and outstanding performance.

Product data

General Information	
Light source replaceable	No
Number of gear units	1 unit
Driver included	No
Light source engine type	LED
Lighting Technology	LED
CE mark	CE mark
Warranty period	3 years
Flammability mark	For mounting on normally flammable surfaces
EU RoHS compliant	Yes
Light Technical	
Luminous Flux	1,000 lm
Standard tilt angle posttop	-

Light Technical		
Luminous Flux	1,000 lm	C
Standard tilt angle posttop	-	D
Standard tilt angle side entry	-	D
Correlated Color Temperature (Nom)	4000 K	c
Luminous Efficacy (rated) (Nom)	104 lm/W	c
Color rendering index (CRI)	80	
Light source color	Neutral white	Ν
Optical cover type	Acrylic bowl/cover clear	F

Operating and Electrical	
Input Voltage	24 DC V
Inrush current	30 A
Inrush time	0.03 ms
Power Consumption	9.6 W
Power Factor (Fraction)	0.95
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug
Temperature	
Ambient temperature range	-40 to +50 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Electronic transformer
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Acrylate

UNIstrip G3

Optical cover material	Acrylate
Housing Color	Aluminum and black
Mounting device	Mounting bracket adjustable
Optical cover shape	Conical
Optical cover finish	Clear
Overall length	335 mm
Overall width	50 mm
Overall height	65 mm
Dimensions (Height x Width x Depth)	65 x 50 x 335 mm

IK06 [1 J]

+/-10%

Safety class III

IP66 [Dust penetration-protected, jet-proof]

Application Conditions	
Maximum dim level Not applicable	
Product Data	
Order product name BCP280 G3 5LEDHP/4000 L300) 24V A
Full product nameBCP280 G3 5LEDHP/4000 L300) 24V A
Full product code 911401622004	
Order code 911401622004	
Material Nr. (12NC) 911401622004	
Numerator - Quantity Per Pack 1	
Numerator - Packs per outer box 8	

Initial Performance (IEC Compliant)


Approval and Application Ingress protection code

Mech. impact protection code

Protection class IEC

Luminous flux tolerance

Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, October 26 - data subject to change