



UNIstrip G3

BCP280 G3 5LEDHP/2700 L300 24V A DMX

UNIstrip G3, 780 lm, 9.6 W, Warm white, Dynamix DMX, Safety class III, Mounting bracket adjustable

UNI strip G3 is a LED wall washer lighting fixture designed for architectural lighting applications. UNIstrip G3 offers reliable quality and outstanding performance.

Product data

General Information Light source replaceable No Number of gear units 1 unit Driver included No Light source engine type LED Lighting Technology LED CE mark CE mark Warranty period 3 years Flammability mark For mounting on normally flammable surf EU RoHS compliant Yes Light Technical Luminous Flux Standard tilt angle posttop - Standard tilt angle side entry -		
Number of gear units 1 unit Driver included No Light source engine type LED Lighting Technology LED CE mark CE mark Warranty period 3 years Flammability mark For mounting on normally flammable surf EU RoHS compliant Yes Light Technical Itaminous Flux Standard tilt angle posttop -	General Information	
Driver included No Light source engine type LED Lighting Technology LED CE mark CE mark Warranty period 3 years Flammability mark For mounting on normally flammable surf EU RoHS compliant Yes Light Technical Image: Calibrid Standard tilt angle posttop	Light source replaceable	No
Light source engine type LED Lighting Technology LED CE mark CE mark Warranty period 3 years Flammability mark For mounting on normally flammable surf EU RoHS compliant Yes Light Technical Image: Compliant of the surf Standard tilt angle posttop -	Number of gear units	1 unit
Lighting Technology LED CE mark CE mark Warranty period 3 years Flammability mark For mounting on normally flammable surf EU RoHS compliant Yes Light Technical Luminous Flux Standard tilt angle posttop -	Driver included	No
CE mark CE mark Warranty period 3 years Flammability mark For mounting on normally flammable surf EU RoHS compliant Yes Light Technical Luminous Flux Standard tilt angle posttop -	Light source engine type	LED
Warranty period 3 years Flammability mark For mounting on normally flammable surf EU RoHS compliant Yes Light Technical Luminous Flux 780 lm Standard tilt angle posttop -	Lighting Technology	LED
Flammability mark For mounting on normally flammable surf EU RoHS compliant Yes Light Technical Luminous Flux 780 lm Standard tilt angle posttop -	CE mark	CE mark
EU RoHS compliant Yes Light Technical Luminous Flux 780 lm Standard tilt angle posttop -	Warranty period	3 years
Light Technical Luminous Flux 780 lm Standard tilt angle posttop -	Flammability mark	For mounting on normally flammable surfaces
Luminous Flux 780 lm Standard tilt angle posttop -	EU RoHS compliant	Yes
Luminous Flux 780 lm Standard tilt angle posttop -		
Standard tilt angle posttop -	Light Technical	
	Luminous Flux	780 lm
Standard tilt angle side entry -	Standard tilt angle posttop	-
	Standard tilt angle side entry	-
		-

Light Technical		
Luminous Flux	780 lm	Cont
Standard tilt angle posttop	-	Dimn
Standard tilt angle side entry	-	Drive
Correlated Color Temperature (Nom)	2700 К	Contr
Luminous Efficacy (rated) (Nom)	81 lm/W	Cons
Color rendering index (CRI)	80	
Light source color	Warm white	Mec
Optical cover type	Acrylic bowl/cover clear	Hous

Operating and Electrical	
Input Voltage	24 DC V
Inrush current	30 A
Inrush time	0.03 ms
Power Consumption	9.6 W
Power Factor (Fraction)	0.95
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug
Temperature	
Ambient temperature range	-40 to +50 °C
Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Electronic transformer
Control interface	Dynamix DMX
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Acrylate

UNIstrip G3

Optical cover material	Acrylate
Housing Color	Aluminum and black
Mounting device	Mounting bracket adjustable
Optical cover shape	Conical
Optical cover finish	Clear
Overall length	335 mm
Overall width	50 mm
Overall height	65 mm
Dimensions (Height x Width x Depth)	65 x 50 x 335 mm

Power consumption tolerance	+/-10%
Application Conditions	
Maximum dim level	0% (digital)
Product Data	
Order product name	BCP280 G3 5LEDHP/2700 L300 24V A DMX
Full product name	BCP280 G3 5LEDHP/2700 L300 24V A DMX
Full product code	911401622304
Order code	01622304
Material Nr. (12NC)	911401622304
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8

Approval and Application


Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class III
Protection class IEC	Safety class III

+/-10%

Initial Performance (IEC Compliant)

Luminous flux tolerance

Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.