



UNIstrip G3

BCP280 G3 5LEDHP/2700 L300 24V A DMX

UNIstrip G3, 780 lm, 9.6 W, Warm white, Dynamix DMX, Safety class III, Mounting bracket adjustable

UNI strip G3 is a LED wall washer lighting fixture designed for architectural lighting applications. UNIstrip G3 offers reliable quality and outstanding performance.

Product data

| General Information | |
|------------------------------------|---|
| Light source replaceable | No |
| Number of gear units | 1 unit |
| Driver included | No |
| Light source engine type | LED |
| Lighting Technology | LED |
| CE mark | CE mark |
| Warranty period | 3 years |
| Flammability mark | For mounting on normally flammable surfaces |
| EU RoHS compliant | Yes |
| | |
| Light Technical | |
| Luminous Flux | 780 lm |
| Standard tilt angle posttop | - |
| Standard tilt angle side entry | - |
| Correlated Color Temperature (Nom) | 2700 K |
| Luminous Efficacy (rated) (Nom) | 81 lm/W |
| Color rendering index (CRI) | 80 |
| Light source color | Warm white |
| Optical cover type | Acrylic bowl/cover clear |
| | |

| Operating and Electrical | |
|-------------------------------|--------------------------|
| Input Voltage | 24 DC V |
| Inrush current | 30 A |
| Inrush time | 0.03 ms |
| Power Consumption | 9.6 W |
| Power Factor (Fraction) | 0.95 |
| Connection | Flying leads/wires |
| Cable | Cable 1.0 m without plug |
| | |
| Temperature | |
| Ambient temperature range | -40 to +50 °C |
| | |
| Controls and Dimming | |
| Dimmable | Yes |
| Driver/power unit/transformer | Electronic transformer |
| Control interface | Dynamix DMX |
| Constant light output | No |
| | |
| Mechanical and Housing | |
| Housing Material | Aluminum extruded |
| Optic material | Acrylate |

Datasheet, 2023, October 26 data subject to change

UNIstrip G3

| Optical cover material | Acrylate | |
|-------------------------------------|--|--|
| Housing Color | Aluminum and black | |
| Mounting device | Mounting bracket adjustable | |
| Optical cover shape | Conical | |
| Optical cover finish | Clear | |
| Overall length | 335 mm | |
| Overall width | 50 mm | |
| Overall height | 65 mm | |
| Dimensions (Height x Width x Depth) | 65 x 50 x 335 mm | |
| | | |
| Approval and Application | | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] | |
| Mech. impact protection code | IK06 [1 J] | |
| Protection class IEC | Safety class III | |
| | | |
| Initial Performance (IEC Compliant) | | |
| Luminous flux tolerance | +/-10% | |

| Power consumption tolerance | +/-10% |
|---------------------------------|--------------------------------------|
| | |
| Application Conditions | |
| Maximum dim level | 0% (digital) |
| | |
| Product Data | |
| Order product name | BCP280 G3 5LEDHP/2700 L300 24V A DMX |
| Full product name | BCP280 G3 5LEDHP/2700 L300 24V A DMX |
| Full product code | 911401622304 |
| Order code | 911401622304 |
| Material Nr. (12NC) | 911401622304 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 8 |
| | |

Dimensional drawing



