

# UNIstrip G3

## BCP280 G3 5LEDHP/2700 L300 24V W

UNIstrip G3, 780 lm, 9.6 W, Warm white, Wide beam angle 45°, Safety class III, Mounting bracket adjustable

UNI strip G3 is a LED wall washer lighting fixture designed for architectural lighting applications. UNIstrip G3 offers reliable quality and outstanding performance.

### Product data

| General Information | |
|---|---|
| **Light source replaceable** | No |
| **Number of gear units** | 1 unit |
| **Driver included** | No |
| **Light source engine type** | LED |
| **Lighting Technology** | LED |
| **CE mark** | CE mark |
| **Warranty period** | 3 years |
| **Flammability mark** | For mounting on normally flammable surfaces |
| **EU RoHS compliant** | Yes |

| Light Technical | |
|---|---|
| **Luminous Flux** | 780 lm |
| **Standard tilt angle posttop** | - |
| **Standard tilt angle side entry** | - |
| **Correlated Color Temperature (Nom)** | 2700 K |
| **Luminous Efficacy (rated) (Nom)** | 81 lm/W |
| **Color rendering index (CRI)** | 80 |
| **Light source color** | Warm white |
| **Optical cover type** | Acrylic bowl/cover clear |

| | |
|---|---|
| **Optic type outdoor** | Wide beam angle 45° |

| Operating and Electrical | |
|---|---|
| **Input Voltage** | 24 DC V |
| **Inrush current** | 30 A |
| **Inrush time** | 0.03 ms |
| **Power Consumption** | 9.6 W |
| **Power Factor (Fraction)** | 0.95 |
| **Connection** | Flying leads/wires |
| **Cable** | Cable 1.0 m without plug |

| Temperature | |
|---|---|
| **Ambient temperature range** | -40 to +50 °C |

| Controls and Dimming | |
|---|---|
| **Dimmable** | No |
| **Driver/power unit/transformer** | Electronic transformer |
| **Control interface** | - |
| **Constant light output** | No |

# UNIstrip G3

| Mechanical and Housing | |
|---|---|
| **Housing Material** | Aluminum extruded |
| **Optic material** | Acrylate |
| **Optical cover material** | Acrylate |
| **Housing Color** | Aluminum and black |
| **Mounting device** | Mounting bracket adjustable |
| **Optical cover shape** | Conical |
| **Optical cover finish** | Clear |
| **Overall length** | 335 mm |
| **Overall width** | 50 mm |
| **Overall height** | 65 mm |
| **Dimensions (Height x Width x Depth)** | 65 x 50 x 335 mm |


| Approval and Application | |
|---|---|
| **Ingress protection code** | IP66 [Dust penetration-protected, jet-proof] |
| **Mech. impact protection code** | IK06 [1 J] |
| **Protection class IEC** | Safety class III |

| Initial Performance (IEC Compliant) | |
|---|---|
| **Luminous flux tolerance** | +/-10% |
| **Power consumption tolerance** | +/-10% |

| Application Conditions | |
|---|---|
| **Maximum dim level** | Not applicable |

| Product Data | |
|---|---|
| **Order product name** | BCP280 G3 5LEDHP/2700 L300 24V W |
| **Full product name** | BCP280 G3 5LEDHP/2700 L300 24V W |
| **Full product code** | 911401622704 |
| **Order code** | 911401622704 |
| **Material Nr. (12NC)** | 911401622704 |
| **Numerator - Quantity Per Pack** | 1 |
| **Numerator - Packs per outer box** | 8 |

## Dimensional drawing




© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.