

# UNIstrip G3

## BCP280 G3 20LEDHP/2700 L1200 24V A

UNI strip G3 is a LED wall washer lighting fixture designed for architectural lighting applications. UNIstrip G3 offers reliable quality and outstanding performance.

### Product data

General Information	
Lamp colour code	Warm white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	ET [ Electronic transformer]
Driver included	No
Optical cover/lens type	ACC [ Acrylic bowl/cover clear]
Control interface	-
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug (C1K)
Protection class IEC	Safety class III (III)
Flammability mark	F [ For mounting on normally flammable surfaces]
CE mark	CE mark
Warranty period	3 years
Constant light output	No
RoHS mark	RoHS mark
LED engine type	LED
Light Technical	
Standard tilt angle post-top	-
Standard tilt angle side entry	-
Operating and Electrical	
Input voltage	24 DC V
Inrush current	30 A

Inrush time	0.03 ms
Power factor (min.)	0.95
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing material	Aluminum extruded
Optic material	Acrylate
Optical cover/lens material	Acrylate
Mounting device	MBA [ Mounting bracket adjustable]
Optical cover/lens shape	Conical
Optical cover/lens finish	Clear
Overall length	1198 mm
Overall width	50 mm
Overall height	65 mm
Colour	Aluminum and black
Approval and Application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]
Initial Performance (IEC Compliant)	
Initial luminous flux	3120 lm
Luminous flux tolerance	+/-10%

## UNIstrip G3

Initial LED luminaire efficacy	78 lm/W
Lamp colour temperature	2700 K
Colour Rendering Index	80
Initial input power	40 W
Power consumption tolerance	+/-10%

### Application Conditions

Ambient temperature range	-40 to +50 °C
Maximum dimming level	Not applicable


### Product Data

Full product code	911401622904
-------------------	--------------

Order product name	BCP280 G3 20LEDHP/2700 L1200 24V A
Order code	911401622904
Numerator – quantity per pack	1
Numerator – packs per outer box	8
Material no. (12NC)	911401622904
Net weight (piece)	1.499 kg



## Dimensional drawing



BCP280/383/384/385 UNIstrip G3

