



Tango Mini BVP280

BVP280 LED42/CW 40W 220-240V AMB MP1

Tango Mini BVP280, 4400 lm, 40 W, Cool white, Asymmetrical medium beam, 39° x 96°, Safety class I, Mounting bracket adjustable

Tango mini LED is a general purpose LED flood lighting luminaire for various lighting applications, such as area lighting, bill-board, façade, industry area and other general applications. The Tango mini LED flood light incorporates LED light source, optical system, heat sink and driver into one compact housing. Its specially designed heat sink incorporates aesthetics and functionality to ensure reliability and long lifetime. Tango mini LED takes advantage of LED technology which provides energy savings and a longer lifetime, bringing area lighting into a new era.

Product data

General Information			
Lamp family code	-	Optical cover type	Polycarbonate micro lens optic
Light source replaceable	Yes	Luminaire light beam spread	39° x 96°
Driver included	Yes	Optic type outdoor	Asymmetrical medium beam
Light source engine type	LED	Operating and Electrical	
Lighting Technology	LED	Input Voltage	220 to 240 V
CE mark	-	Line Frequency	50 or 60 Hz
Warranty period	3 years	Power Consumption	40 W
Light Technical		Power Factor (Fraction)	0.95
Luminous Flux	4,400 lm	Connection	Flying leads/wires
Correlated Color Temperature (Nom)	5700 K	Cable	Cable 0.5 m without plug
Luminous Efficacy (rated) (Nom)	110 lm/W	Temperature	
Color rendering index (CRI)	70	Ambient temperature range	-40 to +50 °C
Light source color	Cool white		

Tango Mini BVP280

Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing	
Housing Material	Aluminum die cast
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Steel
Housing Color	Aluminum and gray
Mounting device	Mounting bracket adjustable
Optical cover finish	Frosted
Overall length	253 mm
Overall width	240 mm
Overall height	47 mm
Effective projected area	0.052 m²
Dimensions (Height x Width x Depth)	47 x 240 x 253 mm

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]

Mech. impact protection code	IK07 [2 J reinforced]
Surge Protection (Common/Differential)	Luminaire surge protection level until 10 kV differential mode and 10 kV common mode
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	SDCM<=7
Power consumption tolerance	+/-10%

Product Data	
Order product name	BVP280 LED42/CW 40W 220-240V AMB MP1
Full product name	BVP280 LED42/CW 40W 220-240V AMB MP1
Full product code	911401632703
Order code	911401632703
Material Nr. (12NC)	911401632703
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

