

# Lighting

**PHILIPS** 

# **SmartBright Road**

# BRP132 LED140/NW 140W 220-240V DM ANZ

SmartBright Road, 14000 lm, 140 W, 740 neutral white, Safety class I, Spigot for diameter 42 to 60 mm

The SmartBright road is ideal for new streets and for renovating existing installations, this affordable range of lighting solutions combines clean, high-quality light with significant energy savings and reduced maintenance.

### **Product data**

General Information	
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Light source engine type	LED
CE mark	CE mark
Warranty period	3 years
EU RoHS compliant	Yes
Light Technical	
Luminous Flux	14,000 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	100 lm/W
Color rendering index (CRI)	70
Light source color	740 neutral white
Optical cover type	Polycarbonate micro lens optic
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz

Initial CLO power consumption	NO W	
Inrush current	10.2 A	
Inrush time	0.066 ms	
Power Consumption	140 W	
Power Factor (Fraction)	0.9	
Connection	Flying leads/wires	
Cable	Cable 0.5 m without plug	
Number of products on MCB of 16 A type B 17		
Temperature		
Ambient temperature range	-40 to +50 °C	
Controls and Dimming		
Dimmable	No	
Control interface	-	
Constant light output	No	
Mechanical and Housing		
Housing Material	Aluminum die cast	
Optic material	Polycarbonate	

# SmartBright Road

Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Dark gray
Mounting device	Spigot for diameter 42 to 60 mm
Overall length	508.2 mm
Overall width	325.5 mm
Overall height	85 mm
Effective projected area	0.14 m²
Dimensions (Height x Width x Depth)	85 x 326 x 508 mm

Initial chromaticity	SDCM>6
Power consumption tolerance	+/-10%
Product Data	
Order product name	BRP132 LED140/NW 140W 220-240V DM
	ANZ
Full product name	BRP132 LED140/NW 140W 220-240V DM
	ANZ
Full product code	911401636504
Order code	911401636504
Material Nr. (12NC)	911401636504
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163319452
Numerator - Packs per outer box	1
EAN/UPC - Case	8710163319452


#### Approval and Application Ingress protection code IP66 [Dust penetration-protected, jet-proof] Mech. impact protection code IK08 [5 J vandal-protected] Surge Protection (Common/Differential) Luminaire surge protection level until 10 kV differential mode and 10 kV common mode Protection class IEC Safety class I

+/-10%

#### Initial Performance (IEC Compliant)

Luminous flux tolerance

## Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, December 5 - data subject to change