



Tango G2 LED

BVP281 LED50/NW 40W 220-240V AMB

Tango G2 LED, 5000 lm, 40 W, Neutral white, Asymmetrical medium beam, 100° x 30°, Safety class I, Mounting bracket adjustable

Tango G2 LED is a general purpose LED flood lighting luminaire for various lighting applications, such as area lighting, bill-board, façade, industry area, recreational sports and other general applications. The Tango G2 LED flood light incorporates LED light source, optical system, heat sink and driver into one compact housing. Its specially designed heat sink incorporates aesthetics and functionality to ensure reliability and long lifetime. Tango G2 LED takes advantage of LED technology which provides energy savings and a longer lifetime, bringing area lighting into a new era.

Product data

| General Information | | | |
|--------------------------|----------|------------------------------------|--------------------------------|
| Lamp family code | - | Standard tilt angle posttop | - |
| Light source replaceable | Yes | Standard tilt angle side entry | - |
| Number of gear units | - | Correlated Color Temperature (Nom) | 4000 K |
| Driver included | Yes | Luminous Efficacy (rated) (Nom) | 125 lm/W |
| Light source engine type | LED | Color rendering index (CRI) | 70 |
| Lighting Technology | LED | Light source color | Neutral white |
| CE mark | CE mark | Optical cover type | Polycarbonate micro lens optic |
| Warranty period | 3 years | Luminaire light beam spread | 100° x 30° |
| Flammability mark | - | Optic type outdoor | Asymmetrical medium beam |
| ENEC mark | - | Operating and Electrical | |
| EU RoHS compliant | No | Input Voltage | 220-240 V |
| Light Technical | | Line Frequency | 50 or 60 Hz |
| Luminous Flux | 5,000 lm | Initial CLO power consumption | - W |
| | | Average CLO power consumption | - W |

Tango G2 LED

| | |
|--|--------------------------|
| End CLO power consumption | - W |
| Power Consumption | 40 W |
| Power Factor (Fraction) | 0.95 |
| Connection | Flying leads/wires |
| Cable | Cable 1.5 m without plug |
| Number of products on MCB of 16 A type B - | |

Temperature

| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Controls and Dimming

| | |
|-------------------------------|----------------------------|
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Control interface | - |
| Constant light output | No |

Mechanical and Housing

| | |
|------------------------|-----------------------------|
| Housing Material | Aluminum die cast |
| Reflector material | - |
| Optic material | Polycarbonate |
| Optical cover material | Polycarbonate |
| Fixation material | Steel |
| Housing Color | Aluminum and gray |
| Mounting device | Mounting bracket adjustable |
| Optical cover shape | - |
| Optical cover finish | Frosted |
| Overall length | 412 mm |
| Overall width | 454 mm |

| | |
|-------------------------------------|-------------------|
| Overall height | 60 mm |
| Effective projected area | 0.133 m² |
| Dimensions (Height x Width x Depth) | 60 x 454 x 412 mm |

Approval and Application

| | |
|--|--|
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK07 [2 J reinforced] |
| Surge Protection (Common/Differential) | Luminaire surge protection level until 10 kV differential mode and 10 kV common mode |
| Protection class IEC | Safety class I |


Initial Performance (IEC Compliant)

| | |
|-----------------------------|---------|
| Luminous flux tolerance | +/-10% |
| Initial chromaticity | SDCM<=7 |
| Power consumption tolerance | +/-10% |

Product Data

| | |
|---------------------------------|----------------------------------|
| Order product name | BVP281 LED50/NW 40W 220-240V AMB |
| Full product name | BVP281 LED50/NW 40W 220-240V AMB |
| Full product code | 872016973010600 |
| Order code | 73010600 |
| Material Nr. (12NC) | 911401661304 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8720169730106 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 8720169730106 |

Dimensional drawing



Tango G2 LED

