



# Tango G2 LED

## BVP282 LED164/WW 160W 220-240V SWB

Tango G2 LED, Safety class I

Tango G2 LED is a general purpose LED flood lighting luminaire for various lighting applications, such as area lighting, bill-board, façade, industry area, recreational sports and other general applications. The Tango G2 LED flood light incorporates LED light source, optical system, heat sink and driver into one compact housing. Its specially designed heat sink incorporates aesthetics and functionality to ensure reliability and long lifetime. Tango G2 LED takes advantage of LED technology which provides energy savings and a longer lifetime, bringing area lighting into a new era.

### Product data

<b>General Information</b>		<b>Optical cover material</b>	
Driver included	Yes	Polycarbonate	
Lighting Technology	LED	<b>Approval and Application</b>	
CE mark	CE mark	Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
<b>Light Technical</b>		Mech. impact protection code	IK07 [2 J reinforced]
Color rendering index (CRI)	80	Protection class IEC	Safety class I
<b>Operating and Electrical</b>		<b>Product Data</b>	
Input Voltage	220-240 V	Order product name	BVP282 LED164/WW 160W 220-240V SWB
Line Frequency	50 to 60 Hz	Full product name	BVP282 LED164/WW 160W 220-240V SWB
<b>Temperature</b>		Full product code	911401665902
Ambient temperature range	-40 to +50 °C	Order code	911401665902
<b>Mechanical and Housing</b>		Material Nr. (12NC)	911401665902
Housing Material	Aluminum extruded	Numerator - Quantity Per Pack	1
Optic material	Polycarbonate	Numerator - Packs per outer box	1

Tango G2 LED

Dimensional drawing

