



# Tango G2 LED

## BVP282 LED176/NW 160W 220-240V SWB

Tango G2 LED, Safety class I

Tango G2 LED is a general purpose LED flood lighting luminaire for various lighting applications, such as area lighting, bill-board, façade, industry area, recreational sports and other general applications. The Tango G2 LED flood light incorporates LED light source, optical system, heat sink and driver into one compact housing. Its specially designed heat sink incorporates aesthetics and functionality to ensure reliability and long lifetime. Tango G2 LED takes advantage of LED technology which provides energy savings and a longer lifetime, bringing area lighting into a new era.

### Product data

General Information	
Driver included	Yes
Lighting Technology	LED
CE mark	CE mark

  

Light Technical	
Color rendering index (CRI)	80

  

Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 to 60 Hz

  

Temperature	
Ambient temperature range	-40 to +50 °C

  

Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Polycarbonate

  

Optical cover material	Polycarbonate
------------------------	---------------

  

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Protection class IEC	Safety class I

  

Product Data	
Order product name	BVP282 LED176/NW 160W 220-240V SWB
Full product name	BVP282 LED176/NW 160W 220-240V SWB
Full product code	911401666302
Order code	911401666302
Material Nr. (12NC)	911401666302
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

# Tango G2 LED

## Dimensional drawing

