



Tango G3 – BVP38x

BVP384 LED600/NW 500W AWB P7 GM

Tango G3 – BVP38x, 60000 lm, 500 W, 740 neutral white, Asymmetrical, 15° x 100°, Analog, Safety class I, Mounting bracket adjustable

The energy-saving Philips Tango G3 LED Floodlight is the ideal solution for a wide range of Area lighting applications. It incorporates the LED light source, optical system, heat sink and driver into one compact and robust housing that meets globally recognized safety standards. Its specially designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, this luminaire delivers superior performance and a longer lifetime, bringing area lighting to a whole new level.

Product data

General Information			
Lamp family code	-	Standard tilt angle posttop	-
Light source replaceable	Yes	Standard tilt angle side entry	-
Number of gear units	-	Correlated Color Temperature (Nom)	4000 K
Driver included	Yes	Luminous Efficacy (rated) (Nom)	120 lm/W
Light source engine type	LED	Color rendering index (CRI)	70
Lighting Technology	LED	Light source color	740 neutral white
CE mark	-	Optical cover type	Polycarbonate micro lens optic
Warranty period	3 years	Luminaire light beam spread	15° x 100°
Flammability mark	-	Optic type outdoor	Asymmetrical
ENEC mark	-		
EU RoHS compliant	No	Operating and Electrical	
		Input Voltage	220 to 240 V
		Line Frequency	50 or 60 Hz
		Inrush current	153 A
		Inrush time	0.585 ms
Light Technical			
Luminous Flux	60,000 lm		

Tango G3 - BVP38x

Power Consumption	500 W
Power Factor (Fraction)	0.9
Connection	Flying leads/wires
Cable	Cable 1.5 m without plug
Number of products on MCB of 16 A type B -	

Temperature

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	Analog
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Steel
Housing Color	Aluminum and gray
Mounting device	Mounting bracket adjustable
Optical cover shape	-
Optical cover finish	-
Overall length	735 mm
Overall width	678 mm
Overall height	221 mm

Dimensions (Height x Width x Depth)	221 x 678 x 735 mm
-------------------------------------	--------------------

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 15 kV differential mode and 15 kV common mode
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	7 SDCM
Power consumption tolerance	+/-10%


Application Conditions

Maximum dim level	10%
-------------------	-----

Product Data

Order product name	BVP384 LED600/NW 500W AWB P7 GM
Full product name	BVP384 LED600/NW 500W AWB P7 GM
Full product code	911401668305
Order code	911401668305
Material Nr. (12NC)	911401668305
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing



Tango G3 - BVP38x

