

FlowBase

BWP352 LED276/NW 240W 220-240V DM MP1 R

FlowBase, 27600 lm, 240 W, 740 neutral white, Medium beam, Safety class I, Wall-mounting bracket

A lighting design that ensures safety and good visibility is a key element in the success of any tunnel project. Philips FlowBase combines compact design, reliability, and affordability in one complete package to bring the perfect lighting solution for any tunnel application.

Product data

General Information	
Light source replaceable	No
Driver included	Yes
Light source engine type	LED
CE mark	CE mark
Light Technical	
Luminous Flux	27,600 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	115 lm/W
Color rendering index (CRI)	>70
Light source color	740 neutral white
Optic type outdoor	Medium beam
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Power Consumption	240 W

0.95

Cable	Cable 0.45 m without plug
Temperature	
Ambient temperature range	-40 to +50 °C
Controls and Dimming	
Dimmable	No
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum die cast
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	Grey
Mounting device	Wall-mounting bracket
Optical cover shape	Ball, globular
Overall length	714 mm
Overall width	300 mm
Overall height	223 mm

Power Factor (Fraction)

FlowBase


Dimensions (Height x Width x Depth)	223 x 300 x 714 mm	
Approval and Application		
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [5 J vandal-protected]	
Protection class IEC	Safety class I	
Initial Performance (IEC Compliant)		
Luminous flux tolerance	+/-5%	
Initial chromaticity	(0.433, 0.401) SDCM>5	

+/-5%

Product Data	
Order product name	BWP352 LED276/NW 240W 220-240V DM MP1 R
Full product name	BWP352 LED276/NW 240W 220-240V DM MP1 R
Full product code	911401672903
Order code	911401672903
Material Nr. (12NC)	911401672903
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

Power consumption tolerance





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.