



GreenVision Xceed

BRP373 LED256/NW 240W 220-240V DM MP1

740 neutral white, 240 W, 220-240 V

GreenVision Xceed offers an affordable LED road lighting solution to the customer for both pedestrian and vehicle road applications. It offers 3 housing sizes and a range of beam optics to fully cater to different road configurations and conditions. It is designed to achieve better light uniformity and maximum spacing between poles, while ensuring sufficient light on the road. Its die-cast aluminum housing and Philips LEDGINE LED platform ensures long lifetime and reliability. Best of all, GreenVision Xceed offers up to 50% of energy savings when compared to conventional lamp systems.

Product data

| General Information | |
|------------------------------------|---|
| Driver included | Yes |
| Flammability mark | For mounting on normally flammable surfaces |
| CE mark | CE mark |
| ENEC mark | - |
| | |
| Light Technical | |
| Luminous Flux | 25,600 lm |
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 106.7 lm/W |
| Color rendering index (CRI) | >70 |
| Light source color | 740 neutral white |
| Optical cover type | Polycarbonate micro lens optic |
| | |
| Operating and Electrical | |
| Input Voltage | 220-240 V |
| Line Frequency | 50 to 60 Hz |

| Power Consumption | 240 W |
|-------------------------------|----------------------------|
| Power Factor (Fraction) | 0.95 |
| Connection | Connection unit 3-pole |
| Cable | - |
| | |
| Temperature | |
| Ambient temperature range | -40 to +50 °C |
| | |
| Controls and Dimming | |
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Control interface | - |
| Constant light output | No |
| | |
| Mechanical and Housing | |
| Housing Material | Aluminum |
| Optic material | Polycarbonate |
| | |

Datasheet, 2023, October 26 data subject to change

GreenVision Xceed

| Optical cover material | Polycarbonate | |
|-------------------------------------|--|--|
| Fixation material | Aluminum | |
| Housing Color | Grey | |
| Effective projected area | 0.271 m² | |
| | | |
| Approval and Application | | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] | |
| Mech. impact protection code | IKO8 [5 J vandal-protected] | |
| Protection class IEC | Safety class I | |
| | | |
| Initial Performance (IEC Compliant) | | |
| Luminous flux tolerance | +/-10% | |
| Initial chromaticity | (0.43, 0.40) SDCM < 5 | |
| Power consumption tolerance | +/-10% | |

| Over Time Performance (IEC Compliant) | | |
|---------------------------------------|---------------------------------------|--|
| Median useful life L70B50 | 100,000 hour(s) | |
| | | |
| Product Data | | |
| Order product name | BRP373 LED256/NW 240W 220-240V DM MP1 | |
| Full product name | BRP373 LED256/NW 240W 220-240V DM MP1 | |
| Full product code | 911401674302 | |
| Order code | 911401674302 | |
| Material Nr. (12NC) | 911401674302 | |
| Numerator - Quantity Per Pack | 1 | |
| Numerator - Packs per outer box | 1 | |

Dimensional drawing









