



# **GreenVision Xceed**

## BRP372 LED138/NW 125W 220-240V DM MP1

740 neutral white, 125 W, 220-240 V

GreenVision Xceed offers an affordable LED road lighting solution to the customer for both pedestrian and vehicle road applications. It offers 3 housing sizes and a range of beam optics to fully cater to different road configurations and conditions. It is designed to achieve better light uniformity and maximum spacing between poles, while ensuring sufficient light on the road. Its die-cast aluminum housing and Philips LEDGINE LED platform ensures long lifetime and reliability. Best of all, GreenVision Xceed offers up to 50% of energy savings when compared to conventional lamp systems.

#### **Product data**

General Information	
Driver included	Yes
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
ENEC mark	-
Light Technical	
Luminous Flux	13,800 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	110.4 lm/W
Color rendering index (CRI)	>70
Light source color	740 neutral white
Optical cover type	Polycarbonate micro lens optic
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 to 60 Hz

Power Consumption	125 W
Power Factor (Fraction)	0.95
Connection	Connection unit 3-pole
Cable	-
Temperature	
Ambient temperature range	-40 to +50 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum
Optic material	Polycarbonate

Datasheet, 2023, September 4 data subject to change

### **GreenVision Xceed**

Optical cover material	Polycarbonate	
Fixation material	Aluminum	
Housing Color	Gray	
Effective projected area	0.166 m²	
Approval and Application		
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [5 J vandal-protected]	
Protection class IEC	Safety class I	
Initial Performance (IEC Compliant)		
Luminous flux tolerance	+/-10%	
Initial chromaticity	(0.43, 0.40) SDCM < 5	
Power consumption tolerance	+/-10%	

Over Time Performance (IEC Compliant)		
Median useful life L70B50	100,000 hour(s)	
Product Data		
Order product name	BRP372 LED138/NW 125W 220-240V DM MP1	
Full product name	BRP372 LED138/NW 125W 220-240V DM MP1	
Full product code	911401675502	
Order code	911401675502	
Material Nr. (12NC)	911401675502	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	1	

#### Dimensional drawing









