



Tango G3 – BVP38x

BVP383 LED270/NW 240W 220-240V AWB

Tango G3 – BVP38x, 27000 lm, 240 W, Neutral white, Asymmetrical wide beam, 15° x 100°, Safety class I, Mounting bracket adjustable

The energy-saving Philips Tango G3 LED Floodlight is the ideal solution for a wide range of Area lighting applications. It incorporates the LED light source, optical system, heat sink and driver into one compact and robust housing that meets globally recognized safety standards. Its specially designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, this luminaire delivers superior performance and a longer lifetime, bringing area lighting to a whole new level.

Product data

General Information			
Light source replaceable	Yes	Luminaire light beam spread	15° x 100°
Driver included	Yes	Optic type outdoor	Asymmetrical wide beam
Light source engine type	LED	Operating and Electrical	
Lighting Technology	LED	Input Voltage	220-240 V
CE mark	-	Line Frequency	50 or 60 Hz
Warranty period	3 years	Power Consumption	240 W
Light Technical		Power Factor (Fraction)	0.95
Luminous Flux	27,000 lm	Connection	Flying leads/wires
Correlated Color Temperature (Nom)	4000 K	Cable	Cable 0.5 m without plug
Luminous Efficacy (rated) (Nom)	110 lm/W	Temperature	
Color rendering index (CRI)	70	Ambient temperature range	-40 to +50 °C
Light source color	Neutral white		
Optical cover type	Polycarbonate micro lens optic		

Tango G3 - BVP38x

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-

Mechanical and Housing

Housing Material	Aluminum die cast
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Steel
Housing Color	Aluminum and gray
Mounting device	Mounting bracket adjustable
Optical cover finish	Frosted
Overall length	591 mm
Overall width	114 mm
Overall height	603 mm
Effective projected area	0.29 m²
Dimensions (Height x Width x Depth)	603 x 114 x 591 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
-------------------------	----------------------------------------------

Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 10 kV differential mode and 10 kV common mode
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	SDCM<=7
Power consumption tolerance	+/-10%

Product Data

Order product name	BVP383 LED270/NW 240W 220-240V AWB
Full product name	BVP383 LED270/NW 240W 220-240V AWB
Full product code	911401682903
Order code	911401682903
Material Nr. (12NC)	911401682903
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

