



# Greenspace Flex

## RS378B P6 927 PSU-E NB M55

Greenspace Flex, 6 W, 927 warm white, Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

### Product data

General Information		Operating and Electrical	
Number of gear units	1 unit	Input Voltage	220 to 240 V
Driver included	Yes	Line Frequency	50 or 60 Hz
Light source engine type	LED	Average CLO power consumption	365 W
CE mark	-	Power Consumption	6 W
Warranty period	3 years	Power Factor (Fraction)	0.9
Flammability mark	-	Connection	External connector
ENEC mark	-	Cable	-
Glow-wire test	Temperature 600 °C, duration 30 s	Number of products on MCB of 16 A type B	-
EU RoHS compliant	Yes		
Light Technical		Temperature	
Luminous Flux	450 lm	Ambient temperature range	-20 to +45 °C
Correlated Color Temperature (Nom)	2700 K		
Luminous Efficacy (rated) (Nom)	75 lm/W	Controls and Dimming	
Color rendering index (CRI)	>90	Dimmable	No
Beam angle of light source	- degree(s)	Driver/power unit/transformer	Electronic transformer
Light source color	927 warm white	Control interface	-
Optic type	-	Constant light output	No
Optical cover type	-		
		Mechanical and Housing	
		Housing Material	Aluminum Alloy

Greenspace Flex

Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover material	-
Fixation material	Aluminum
Housing Color	Dark gray
Optical cover finish	-
Overall height	49 mm
Overall diameter	55 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK04 [0.5 J standard plus]
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	SDCM<3
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Median useful life L80B50	50.000 hour(s)
---------------------------	----------------



Application Conditions

Maximum dim level	Not applicable
Suitable for random switching	No

Product Data

Order product name	RS378B P6 927 PSU-E NB M55
Full product name	RS378B P6 927 PSU-E NB M55
Full product code	911401720892
Order code	911401720892
Material Nr. (12NC)	911401720892
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	48

Dimensional drawing



Modular Type	D, mm	H, mm
RS378B P6/P11 M55	55	49
RS378B P15 M55	55	49
RS378B P24 M70	70	90
RS378B P33 M87	87	107
RS378B P42 M102	102	116

