



# Essential SmartBright G2 LED Security Light

## BVP133 LED24/WW 30W 220-240V WB PIR

Essential SmartBright G2 LED Security Light, 2400 lm, 30 W, 830 warm white, 100°, Safety class I, Mounting bracket adjustable

The Essential SmartBright G2 LED security light is a motion sensor activated security light, with a built-in PIR sensor and Lux sensor, automatic and instant-on when motion detected, assuring your property is well lit for visibility at. night and dusk.

### Product data

General Information	
Lamp family code	LED24 [LED Module 2400 lm]
Light source replaceable	No
Driver included	Yes
Light source engine type	LED
Lighting Technology	LED
CE mark	CE mark
Flammability mark	For mounting on normally flammable
	surfaces
ENEC mark	-
Light Technical	
Luminous Flux	2,400 lm
Standard tilt angle posttop	-
Standard tilt angle side entry	-
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	80 lm/W
Color rendering index (CRI)	>80
·	·

Light source color	830 warm white	
Optical cover type	Polycarbonate bowl/cover UV-resistant	
Luminaire light beam spread	100°	
Operating and Electrical		
Input Voltage	220 to 240 V	
Line Frequency	50 to 60 Hz	
Inrush current	2.66 A	
Inrush time	0.016 ms	
Power Consumption	30 W	
Power Factor (Fraction)	0.9	
Connection	Flying leads/wires	
Cable	Cable 0.25m without plug	
Number of products on MCB of 16 A type B 80		
Temperature		
Ambient temperature range	-40 to +45 °C	

Datasheet, 2023, December 5 data subject to change

# **Essential SmartBright G2 LED Security Light**


Controls and Dimming	
Dimmable	No
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum die cast
Optical cover material	Polycarbonate
Housing Color	Black
Mounting device	Mounting bracket adjustable
Optical cover finish	Textured
Overall length	170 mm
Overall width	146 mm
Overall height	36 mm
Effective projected area	0.028 m²
Dimensions (Height x Width x Depth)	36 x 146 x 170 mm
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]

IK06 [1 J]

Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	SDCM <7
Power consumption tolerance	+/-10%
Product Data	
Order product name	BVP133 LED24/WW 30W 220-240V WB PIR
Full product name	BVP133 LED24/WW 30W 220-240V WB PIR
Full product code	871016332323799
Order code	911401722492
Material Nr. (12NC)	911401722492
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163323237
Numerator - Packs per outer box	12
EAN/UPC - Case	8710163323534

### Dimensional drawing

Mech. impact protection code





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.