



# SmartBright Suspension

## RC095V LED15S/865 PSU W12L60 Grey GM

SmartBright Suspension, 88 lm/W, 840 neutral white

Linear suspension solution with affordable price

### Product data

General Information		Luminaire light beam spread	
Light source replaceable	No	120°	
Number of gear units	1 unit	Operating and Electrical	
Driver included	Yes	Input Voltage	220 to 240 V
Light source engine type	LED	Line Frequency	50 or 60 Hz
CE mark	-	Inrush current	6.4 A
Warranty period	3 years	Inrush time	0.0069 ms
Flammability mark	-	Power Consumption	17 W
ENEC mark	-	Power Factor (Fraction)	0.9
Glow-wire test	Temperature 650 °C, duration 30 s	Connection	-
EU RoHS compliant	Yes	Cable	Cable 1.0 m without plug
Light Technical		Number of products on MCB of 16 A type B 210	
Luminous Flux	1,500 lm	Temperature	
Correlated Color Temperature (Nom)	4000 K	Ambient temperature range	-10 to +35 °C
Luminous Efficacy (rated) (Nom)	88 lm/W	Controls and Dimming	
Color rendering index (CRI)	>80	Dimmable	No
Beam angle of light source	- degree(s)	Driver/power unit/transformer	Power supply unit (On/Off)
Light source color	840 neutral white	Control interface	-
Optic type	Symmetrical		
Optical cover type	Polystyrene bowl/cover prismatic		

SmartBright Suspension

Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	-
Optic material	Polystyrene
Optical cover material	Polystyrene
Fixation material	Stainless steel
Housing Color	Gray
Optical cover finish	Frosted
Overall length	600 mm
Overall width	120 mm
Overall height	65 mm
Dimensions (Height x Width x Depth)	65 x 120 x 600 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

Initial chromaticity	≤5
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Median useful life L70B50	25,000 hour(s)
Application Conditions	
Maximum dim level	Not applicable
Suitable for random switching	No
Product Data	
Order product name	RC095V LED15S/865 PSU W12L60 Grey GM
Full product name	RC095V LED15S/865 PSU W12L60 Grey GM
Full product code	871016332464700
Order code	911401723742
Material Nr. (12NC)	911401723742
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169732056
Numerator - Packs per outer box	1
EAN/UPC - Case	8710163324647

Dimensional drawing

