



LED Marker

BBG152 LED50/WW PSU 220-240V IP67

LED Marker, 55 lm, 2.5 W, 830 warm white, Safety class I, Allen screw fixation

People want to create a pleasant atmosphere around their property – something that will catch visitors' attention, make them feel good and want to come back again. They would like to be able to create an appealing ambience at minimum cost, though without compromising on the quality of the lighting. Combining a simple design with reliable lighting performance, this low-cost white-light LED marker delivers a glare-free soft light effect.

Product data

| | | | |
|------------------------------------|---|---|--|
| General Information | | Light source color | |
| Lamp family code | LED-LP [LED Low Power] | 830 warm white | |
| Light source replaceable | No | Optical cover type | |
| Number of gear units | 1 unit | Front-glass uplighting version | |
| Driver included | Yes | Operating and Electrical | |
| Light source engine type | LED | Input Voltage | |
| CE mark | CE mark | 220 to 240 V | |
| Warranty period | 1 years | Line Frequency | |
| Flammability mark | For mounting on normally flammable surfaces | 50 to 60 Hz | |
| Light Technical | | Power Consumption | |
| Luminous Flux | 55 lm | 2.5 W | |
| Correlated Color Temperature (Nom) | 3000 K | Power Factor (Fraction) | |
| Luminous Efficacy (rated) (Nom) | 22.00 lm/W | 0.35 | |
| Color rendering index (CRI) | >80 | Connection | |
| Number of light sources | 30 | Screw connection block | |
| | | Cable | |
| | | Cable without plug 3-pole | |
| | | Number of products on MCB of 16 A type B | |
| | | 1 | |
| | | Temperature | |
| | | Ambient temperature range | |
| | | -20 to +40 °C | |
| | | Controls and Dimming | |
| | | Dimmable | |
| | | No | |

LED Marker

| | |
|-------------------------------|----------------------------|
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Control interface | - |
| Constant light output | No |

Mechanical and Housing

| | |
|------------------------|----------------------|
| Housing Material | Aluminum die cast |
| Optical cover material | Tempered glass |
| Housing Color | Dark gray |
| Mounting device | Allen screw fixation |
| Optical cover finish | Matte |
| Overall height | 137 mm |
| Overall diameter | 153 mm |

Approval and Application

| | |
|------------------------------|---|
| Ingress protection code | IP67 [Dust penetration-protected, watertight] |
| Mech. impact protection code | IK10 [20 J vandal-resistant] |
| Protection class IEC | Safety class I |

| | |
|-------------------------------------|--------|
| Initial Performance (IEC Compliant) | |
| Luminous flux tolerance | +/-10% |
| Power consumption tolerance | +/-10% |

Product Data

| | |
|---------------------------------|-----------------------------------|
| Order product name | BBG152 LED50/WW PSU 220-240V IP67 |
| Full product name | BBG152 LED50/WW PSU 220-240V IP67 |
| Full product code | 87201695323599 |
| Order code | 53233599 |
| Material Nr. (12NC) | 911401723901 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8720169532335 |
| Numerator - Packs per outer box | 12 |
| EAN/UPC - Case | 8720169543829 |

Dimensional drawing

