PHILIPS Lighting



UNIIn-ground

BBP343 LED B 18W 20D 100-240V

UNIIn-ground, 400 lm, 18 W, Blue, Safety class I, Recessed mounting box round

UNIIn-ground family provide a completed range of up-lights in terms of wattage, beam angle, color temperature, etc. It is to make your space distinctive with more safety and convenience as well. Compact and robust design with aluminum housing, waterproof connectors are all for ensuring long-lasting operation without your more caring after installation. Waterproof connector is to give more ease to installation and save your installation cost. Apart from high-quality white light, RGB (and mono RGB) are available with DMX512 decoder built-in side.

Product data

General Information		
Light source replaceable	No	
Driver included	Yes	
Light source engine type	LED	
CE mark	-	
Flammability mark	For mounting on normally flammable surfaces	
Light Technical		
Luminous Flux	400 lm	
Standard tilt angle posttop	-	
Correlated Color Temperature (Nom)	-	
Luminous Efficacy (rated) (Nom)	22 lm/W	
Color rendering index (CRI)	-	
Light source color	Blue	
Optical cover type	Glass	

Operating and Electrical		
Input Voltage	100 to 240 V	
input voltage	100 to 240 V	
Line Frequency	50 or 60 Hz	
Power Consumption	18 W	
Power Factor (Fraction)	0.9	
Connection	Screw connection block 3-pole	
Cable	Cable 0.3 m with connector 3-pole	
Temperature		
Ambient temperature range	-40 to +50 °C	
Controls and Dimming		
Dimmable	No	
Control interface	-	

UNIIn-ground

Mechanical and Housing		
Housing Material	Aluminum	
Optic material	Polycarbonate	
Optical cover material	Polycarbonate	
Housing Color	Steel	
Mounting device	Recessed mounting box round	
Optical cover finish	Clear	
Overall height	152 mm	
Overall diameter	180 mm	
Approval and Application		

IP67 [Dust penetration-protected, watertight]

IK10 [20 J vandal-resistant]

Safety class I

+/-10%

Initial chromaticity	-	
Power consumption tolerance	+/-10%	
Product Data		
Order product name	BBP343 LED B 18W 20D 100-240V	
Full product name	BBP343 LED B 18W 20D 100-240V	
Full product code	871951494829799	
Order code	911401755412	
Material Nr. (12NC)	911401755412	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8719514948297	
Numerator - Packs per outer box	4	
EAN/UPC - Case	8719514948372	

Dimensional drawing


Ingress protection code

Protection class IEC

Luminous flux tolerance

Mech. impact protection code

Initial Performance (IEC Compliant)



Product Type	Ø, mm	H, mm
BBP340	100	140
BBP341	120	145
BBP342	140	150
BBP343	180	175
BBP344	250	185





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, October 17 - data subject to change