



# Essential SmartBright LED Downlight

## DN027B LED9/WW L150 SQ

Essential SmartBright G2 LED Downlight is value for money product with high efficacy, good quality and reliability. It offers multiple configurations from 300lm to 2000lm output, to replace conventional downlight. It can be used for shopping mall, retail store, residential and office. It's an ideal product family to distribute in trade market.

### **Product data**

General Information		
Light source replaceable	No	
Lighting Technology	LED	
Warranty period	1 years	
Light Technical		
Luminous Flux	900 lm	
Correlated Color Temperature (Nom)	3000 K	
Color rendering index (CRI)	80	
Light source color	3000/4000/6500	
Luminaire light beam spread	110°	
Operating and Electrical		
Line Frequency	50 or 60 Hz	
Input Frequency	50 or 60 Hz	
Power Consumption	11 W	
Power Factor (Fraction)	0.7	
Connection	Flying leads/wires	


Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Mechanical and Housing	
Housing Material	Plastic
Reflector material	Polycarbonate
Optic material	Polycarbonate
Housing Color	White
Overall length	175 mm
Overall width	175 mm
Overall height	33 mm
Overall diameter	225 mm
Dimensions (Height x Width x Depth)	33 x 175 x 175 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]

## Essential SmartBright LED Downlight


Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class II
Initial Performance (IEC Compliant)	
Initial chromaticity	SDCM<5
Power consumption tolerance	+/-10%
Product Data	
Order product name	DN027B LED9/WW L150 SQ
Full product name	DN027B LED9/WW L150 SQ

Full product code	871016330916399
Order code	911401815097
Material Nr. (12NC)	911401815097
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163309163
Numerator - Packs per outer box	24
EAN/UPC - Case	8710163310046

## **Dimensional drawing**



### Photometric data



Light Distribution Diagram - DN027B LED9/WW L150 SQ

		150 SQ 1 x 911401315097 3008K 1 x 1021 in
	Provide the second seco	
<pre>ipingent in</pre>		

General uniform lighting - DN027B LED9/WW L150 SQ



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 30 - data subject to change