



GreenVision Xceed

BRP373 LED203/WW 185W 220-240V DM MP1

GreenVision Xceed, 20350 lm, 185 W, 730 warm white, Safety class I, Side-entry for diameter 48 to 60 mm

GreenVision Xceed offers an affordable LED road lighting solution to the customer for both pedestrian and vehicle road applications. It offers 3 housing sizes and a range of beam optics to fully cater to different road configurations and conditions. It is designed to achieve better light uniformity and maximum spacing between poles, while ensuring sufficient light on the road. Its die-cast aluminum housing and Philips LEDGINE LED platform ensures long lifetime and reliability. Best of all, GreenVision Xceed offers up to 50% of energy savings when compared to conventional lamp systems.

Product data

General Information		Light source color	
Light source replaceable	Yes	Optical cover type	Clear glass
Number of gear units	2 units	Operating and Electrical	
Driver included	Yes	Input Voltage	220 to 240 V
Light source engine type	LED	Line Frequency	50 to 60 Hz
CE mark	CE mark	Power Consumption	185 W
Warranty period	3 years	Power Factor (Fraction)	0.9
Light Technical		Temperature	
Luminous Flux	20,350 lm	Ambient temperature range	-40 to +50 °C
Standard tilt angle posttop	0°	Controls and Dimming	
Standard tilt angle side entry	0°	Dimmable	No
Correlated Color Temperature (Nom)	3000 K	Driver/power unit/transformer	Power supply unit (On/Off)
Luminous Efficacy (rated) (Nom)	110 lm/W		
Color rendering index (CRI)	70		

GreenVision Xceed

Constant light output	No
-----------------------	----

Mechanical and Housing

Housing Material	Aluminum die cast
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Grey
Mounting device	Side-entry for diameter 48 to 60 mm
Optical cover shape	Ball, globular
Optical cover finish	Clear
Overall length	853 mm
Overall width	318 mm
Overall height	136 mm
Effective projected area	0.271 m²
Dimensions (Height x Width x Depth)	136 x 318 x 853 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Philips standard surge protection level

Protection class IEC	Safety class I
----------------------	----------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-5%
Initial chromaticity	SDCM>5
Power consumption tolerance	+/-5%

Application Conditions

Maximum dim level	Not applicable
-------------------	----------------

Product Data

Order product name	BRP373 LED203/WW 185W 220-240V DM MPI
Full product name	BRP373 LED203/WW 185W 220-240V DM MPI
Full product code	911401830598
Order code	911401830598
Material Nr. (12NC)	911401830598
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

