



Xtend LED

RC115B LED35S/840 PSU W60L120 S

Xtend LED, 95 lm/W, 840 neutral white

Xtend LED is the new generation of linear design troffer with good illuminating uniformity and high efficiency

Product data

General Information	
Lamp family code	LED22 [LED module 2200 lm]
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Light source engine type	LED
CE mark	CE mark
ENEC mark	-
Glow-wire test	Temperature 650 °C, duration 30 s
Light Technical	
Luminous Flux	3,500 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	95 lm/W
Color rendering index (CRI)	80
Light source color	840 neutral white
Optic type	Beam angle 60 to 120°
Optical cover type	Acrylic bowl/cover
Luminaire light beam spread	110° x 110°
Operating and Electrical	
Input Voltage	220-240 V

Line Frequency	50 or 60 Hz
Power Consumption	36.5 W
Power Factor (Fraction)	0.9
Number of products on MCB of 16 A type B	21
Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	Yes
Mechanical and Housing	
Housing Material	Steel
Reflector material	Steel
Optic material	Polymethyl methacrylate
Optical cover material	Acrylate
Housing Color	White
Optical cover finish	Frosted

Xtend LED

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	RC115B LED35S/840 PSU W60L120 S

Full product name	RC115B LED35S/840 PSU W60L120 S
Full product code	911401830899
Order code	01830899
Material Nr. (12NC)	911401830899
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2

Dimensional drawing

