



GreenVision Xceed

BRP371 LED103/NW 90W 220-240V DM MP1

GreenVision Xceed, 10350 lm, 90 W, 740 neutral white, Safety class I, Side-entry for diameter 48 to 60 mm

GreenVision Xceed offers an affordable LED road lighting solution to the customer for both pedestrian and vehicle road applications. It offers 3 housing sizes and a range of beam optics to fully cater to different road configurations and conditions. It is designed to achieve better light uniformity and maximum spacing between poles, while ensuring sufficient light on the road. Its die-cast aluminum housing and Philips LEDGINE LED platform ensures long lifetime and reliability. Best of all, GreenVision Xceed offers up to 50% of energy savings when compared to conventional lamp systems.

Product data

General Information		Light source color	
Light source replaceable	Yes	Light source color	740 neutral white
Number of gear units	1 unit	Optical cover type	Clear glass
Driver included	Yes	Operating and Electrical	
Light source engine type	LED	Input Voltage	220 to 240 V
CE mark	CE mark	Line Frequency	50 to 60 Hz
Warranty period	3 years	Power Consumption	90 W
		Power Factor (Fraction)	0.9
Light Technical		Temperature	
Luminous Flux	10,350 lm	Ambient temperature range	-40 to +50 °C
Standard tilt angle posttop	0°	Controls and Dimming	
Standard tilt angle side entry	0°	Dimmable	No
Correlated Color Temperature (Nom)	4000 K	Driver/power unit/transformer	Power supply unit (On/Off)
Luminous Efficacy (rated) (Nom)	115 lm/W		
Color rendering index (CRI)	70		

GreenVision Xceed

Constant light output	No
-----------------------	----

Mechanical and Housing

Housing Material	Aluminum die cast
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Grey
Mounting device	Side-entry for diameter 48 to 60 mm
Optical cover shape	Ball, globular
Optical cover finish	Clear
Overall length	422 mm
Overall width	318 mm
Overall height	136 mm
Effective projected area	0.134 m ²
Dimensions (Height x Width x Depth)	136 x 318 x 422 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Philips standard surge protection level

Protection class IEC	Safety class I
----------------------	----------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-5%
Initial chromaticity	SDCM>5
Power consumption tolerance	+/-5%

Application Conditions

Maximum dim level	Not applicable
-------------------	----------------

Product Data

Order product name	BRP371 LED103/NW 90W 220-240V DM MP1
Full product name	BRP371 LED103/NW 90W 220-240V DM MP1
Full product code	911401832098
Order code	911401832098
Material Nr. (12NC)	911401832098
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

