



SmartBright Panel

RC099V LED36S/840 W60L60 GM

SmartBright Panel, 840 neutral white

SmartBright Panel is the most affordable LED panel delivering comfortable light with excellent uniformity

Product data



General Information		Controls and Dimming	
Light source replaceable	No	Dimmable	No
Number of gear units	1 unit	Driver/power unit/transformer	Power supply unit (On/Off)
Driver included	Yes	Constant light output	Yes
CE mark	CE mark		
ENEC mark	-		
Glow-wire test	Temperature 650 °C, duration 30 s		
Light Technical		Mechanical and Housing	
Correlated Color Temperature (Nom)	4000 K	Housing Material	Steel
Color rendering index (CRI)	80	Reflector material	Steel
Number of light sources	12	Optic material	Polycarbonate
Light source color	840 neutral white	Housing Color	White
Optic type	Beam angle 60 to 120°		
Optical cover type	Transparent bowl with white cover		
Luminaire light beam spread	110° x 110°		
Operating and Electrical		Approval and Application	
Input Voltage	220-240 V	Ingress protection code	IP20 [Finger-protected]
Power Consumption	34 W	Mech. impact protection code	IK02 [0.2 J standard]
Power Factor (Fraction)	0.9	Protection class IEC	Safety class I
		Initial Performance (IEC Compliant)	
		Luminous flux tolerance	+/-10%
		Power consumption tolerance	+/-10%
		Product Data	
		Order product name	RC099V LED36S/840 W60L60 GM

Full product name	RC099V LED36S/840 W60L60 GM
Full product code	911401835199
Order code	911401835199
Material Nr. (12NC)	911401835199

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2

Dimensional drawing

Product Type	Size LxWxH(mm)
RC099V LED36S W60x60 GM	597x297x75
RC099V LED36S W60x120 GM	1197x297x75
RC099V LED36S W60x60 SUS GM	603x603x75
RC099V LED36S W60x120 SUS GM	1203x603x75
RC099V LED36S W60x60 PCV GM	603x603x75
RC099V LED36S W60x120 PCV GM	1203x603x75
RC099V LED36S W60x60 GM	597x297x75
RC099V LED36S W60x120 GM	1197x297x75
RC099V LED36S W60x60 SUS GM	603x603x75
RC099V LED36S W60x120 SUS GM	1203x603x75
RC099V LED36S W60x60 PCV GM	603x603x75
RC099V LED36S W60x120 PCV GM	1203x603x75



RC099V LED36S W60x60 GM
RC099V LED36S W60x120 SUS GM
RC099V LED36S W60x60 PCV GM
RC099V LED36S W60x120 SUS GM
RC099V LED36S W60x60 PCV GM

RC099V LED36S W60x120 GM
RC099V LED36S W60x120 SUS GM
RC099V LED36S W60x120 PCV GM
RC099V LED36S W60x120 SUS GM
RC099V LED36S W60x120 PCV GM

