



SmartBright Panel

RC099V LED36S/840 W60L60 PCV GM

SmartBright Panel, 840 neutral white

SmartBright Panel is the most affordable LED panel delivering comfortable light with excellent uniformity

Product data

General Information				
Light source replaceable	No			
Number of gear units	1 unit			
Driver included	Yes			
CE mark	CE mark			
ENEC mark	-			
Glow-wire test	Temperature 650 °C, duration 30 s			
Light Technical				
Correlated Color Temperature (Nom)	4000 K			
Color rendering index (CRI)	80			
Number of light sources	12			
Light source color	840 neutral white			
Optic type	Beam angle 60 to 120°			
Optical cover type	Transparent bowl with white cover			
Luminaire light beam spread	110° x 110°			
Operating and Electrical				
Input Voltage	220-240 V			
Power Consumption	34 W			
Power Factor (Fraction)	0.9			

Controls and Dimming			
Dimmable	No		
Driver/power unit/transformer	Power supply unit (On/Off)		
Constant light output	Yes		
Mechanical and Housing			
Housing Material	Steel		
Reflector material	Steel		
Optic material	Polycarbonate		
Housing Color	White		
Approval and Application			
Ingress protection code	IP20 [Finger-protected]		
Mech. impact protection code	IK02 [0.2 J standard]		
Protection class IEC	Safety class I		
Initial Performance (IEC Compliant)			
Luminous flux tolerance	+/-10%		
Power consumption tolerance	+/-10%		
Product Data			
Order product name	RC099V LED36S/840 W60L60 PCV GM		

Datasheet, 2023, April 30 data subject to change


SmartBright Panel

Full product name	RC099V LED36S/840 W60L60 PCV GM			
Full product code	911401835999			
Order code	01835999			
Material Nr. (12NC)	911401835999			

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2

Dimensional drawing

Product Type	Size LxWxH(mm)			
RC099V LED26S W60L60 GM	597x597x75			
RC099V LED26S W30L120 GM	1197x297x75			
RC099V LED26S W60L60 SUS GM	603x603x75			
RC099V LED26S W30L120 SUS GM	1203x303x75			
RC099V LED26S W60L60 PCV GM	603x603x75			
RC099V LED26S W30L I20 PCV GM	1203×303×75			
RC099V LED36S W60L60 GM	597x597x75			
RC099V LED36S W30L120 GM	1197x297x75			
RC099V LED36S W60L60 SUS GM	603x603x75			
RC099V LED36S W30L120 SUS GM	1203x303x75			
RC099V LED36S W60L60 PCV GM	603x603x75			
RC099V LED36S W30L120 PCV GM	1203×303×75			
	RCD99V LED26S W46 RCD99V LED26S W46 RCD99V LED36S W46 RCD99V LED36S W46 RCD99V LED36S W46 RCD99V LED36S W46	LSO SUS GM LSO PCV GM LSO GM LSO SUS GM	ACOWN LIDISS WARL 130 OH ACOWN LIDISS WARL 130 DIS CH ACOWN LIDISS WARL 130 DIS CH ACOWN LIDISS WARL 130 DIS CH ACOWN LIDISS WARL 130 CH ACOWN LID	





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.