



UNIstrip LP G2

BCP270 G2 48xLED/5000 24V L1200 A RU

UNIstrip LP G2, 1320 lm, 15.5 W, Cool white, Safety class III,
Mounting bracket adjustable

UNIstrip LP Gen2 is an evolution in both optical and system design. It offers Mono and RGB DMX versions with precision optical performance to enable dynamic effects with affordable pricing.

Product data

General Information		Optical cover type		Polycarbonate linear
Light source replaceable	No	Operating and Electrical		
Number of gear units	1 unit	Input Voltage	24 DC V	
Driver included	No	Power Consumption	15.5 W	
Light source engine type	LED	Power Factor (Fraction)	0.9	
Lighting Technology	LED	Connection	Flying leads/wires	
CE mark	-	Cable	Cable 1.0 m without plug	
Warranty period	3 years	Temperature		
Flammability mark	For mounting on normally flammable surfaces	Ambient temperature range	-40 to +50 °C	
ENEC mark	-	Controls and Dimming		
EU RoHS compliant	Yes	Dimmable	No	
Light Technical		Driver/power unit/transformer	Electronic transformer	
Luminous Flux	1,320 lm	Control interface	-	
Standard tilt angle posttop	-	Constant light output	No	
Standard tilt angle side entry	-	Mechanical and Housing		
Correlated Color Temperature (Nom)	5000 K	Housing Material	Aluminum extruded	
Luminous Efficacy (rated) (Nom)	85 lm/W			
Color rendering index (CRI)	70			
Light source color	Cool white			

UNIstrip LP G2

Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Aluminum and black
Mounting device	Mounting bracket adjustable
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	1,216 mm
Overall width	50 mm
Overall height	61 mm
Dimensions (Height x Width x Depth)	61 x 50 x 1216 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class III

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Application Conditions	
Maximum dim level	Not applicable

Product Data	
Order product name	BCP270 G2 48xLED/5000 24V L1200 A RU
Full product name	BCP270 G2 48xLED/5000 24V L1200 A RU
Full product code	911401855798
Order code	911401855798
Material Nr. (12NC)	911401855798
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8

Dimensional drawing

