



# UNistrip LP G2

## BCP270 G2 18xLED/RGB 24V L300 A DMX RU

UNistrip LP Gen2 is an evolution in both optical and system design. It offers Mono and RGB DMX versions with precision optical performance to enable dynamic effects with affordable pricing.

### Product data

General Information	
Light source color	Red, green and blue
Number of gear units	1 unit
Driver/power unit/transformer	Electronic transformer
Driver included	No
Optical cover/lens type	Polycarbonate linear
Control interface	Dynamix DMX
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug
Protection class IEC	Safety class III
Flammability mark	For mounting on normally flammable surfaces
CE mark	-
ENEC mark	-
Warranty period	3 years
Constant light output	No
RoHS mark	RoHS mark
Light source engine type	LED
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Aluminum extruded

Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Aluminum
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	329 mm
Overall width	50 mm
Overall height	61 mm

### Approval and Application

Mech. impact protection code	IK03 [ 0.3 J]
------------------------------	---------------

### Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	120 lm
Initial LED luminaire efficacy	30 lm/W
Init. Corr. Color Temperature	- K
Initial input power	4 W
Power consumption tolerance	+/-10%

### Application Conditions

Ambient temperature range	-40 to +50 °C
---------------------------	---------------


UNIstrip LP G2

Maximum dim level	0% (digital)
Product Data	
Full product code	911401856398
Order product name	BCP270 G2 18xLED/RGB 24V L300 A DMX RU
Order code	911401856398
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	18
Material Nr. (12NC)	911401856398
Net Weight (Piece)	0.459 kg



Dimensional drawing



UNIstrip LP G2 BCP270

