



# UNIstrip LP G2

## BCP270 G2 12xLED/5000 24V L300 A DMX RU

UNIstrip LP G2, 330 lm, 3.4 W, Cool white, Dynamix DMX, Safety class III, Mounting bracket adjustable

UNIstrip LP Gen2 is an evolution in both optical and system design. It offers Mono and RGB DMX versions with precision optical performance to enable dynamic effects with affordable pricing.

### Product data

<b>General Information</b>		<b>Optical cover type</b>	
Light source replaceable	No	Polycarbonate linear	
Number of gear units	1 unit	<b>Operating and Electrical</b>	
Driver included	No	Input Voltage	24 DC V
Light source engine type	LED	Power Consumption	3.4 W
Lighting Technology	LED	Power Factor (Fraction)	0.9
CE mark	-	Connection	Flying leads/wires
Warranty period	3 years	Cable	Cable 1.0 m without plug
Flammability mark	For mounting on normally flammable surfaces	<b>Temperature</b>	
ENEC mark	-	Ambient temperature range	-40 to +50 °C
EU RoHS compliant	Yes	<b>Controls and Dimming</b>	
<b>Light Technical</b>		Dimmable	Yes
Luminous Flux	330 lm	Driver/power unit/transformer	Electronic transformer
Standard tilt angle posttop	-	Control interface	Dynamix DMX
Standard tilt angle side entry	-	Constant light output	No
Correlated Color Temperature (Nom)	5000 K	<b>Mechanical and Housing</b>	
Luminous Efficacy (rated) (Nom)	97 lm/W	Housing Material	Aluminum extruded
Color rendering index (CRI)	70		
Light source color	Cool white		

UNIstrip LP G2

Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Aluminum and black
Mounting device	Mounting bracket adjustable
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	329 mm
Overall width	50 mm
Overall height	61 mm
Dimensions (Height x Width x Depth)	61 x 50 x 329 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class III

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Application Conditions	
Maximum dim level	0% (digital)

Product Data	
Order product name	BCP270 G2 12xLED/5000 24V L300 A DMX RU
Full product name	BCP270 G2 12xLED/5000 24V L300 A DMX RU
Full product code	911401856498
Order code	911401856498
Material Nr. (12NC)	911401856498
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	18

Dimensional drawing

