



# CityCurve gen2

## BSP295 GRN24/830 PSR-CLO WSO II 7035

CityCurve gen 2, LED GreenLine 2400 lm, 830 warm white, Power supply unit regulating with constant light output, Safety class II, Wide street optic

Offering a contemporary interpretation of the old 'bell'-shaped street light, CityCurve gen2, with its retro appearance, fits both modern urban spaces as well as historical environments. Its LED module allows cities to focus on reducing energy consumption. Designed for installation at heights of 4 to 6 meters, and offering a wide choice of brackets and columns, CityCurve gen2 is ideal for lighting urban centers and streets, pedestrian areas, squares and parks.

#### **Product data**

| General Information                                  |                                  |
|--|----------------------------------|
| Lamp family code                                     | GRN24 [LED GreenLine 2400 lm]    |
| Light source replaceable                             | Yes                              |
| Driver included                                      | Yes                              |
| Product family code                                  | BSP295 [CityCurve gen 2]         |
| Lighting Technology                                  | LED                              |
| CE mark  | Yes                              |
| ENEC mark  | ENEC mark                        |
| Glow-wire test                                       | Temperature 650 °C, duration 5 s |
|  |                                  |
| Light Technical                                      |                                  |
| Luminous Flux  | 1,944 lm                         |
| Correlated Color Temperature (Nom)                   | 3000 K                           |
| Luminous Efficacy (rated) (Nom)                      | 67 lm/W                          |
|  |                                  |
| Color rendering index (CRI)                          | 84                               |
| Color rendering index (CRI)  Number of light sources | 24                               |

| Light source color        | 830 warm white                 |
|---------------------------|--------------------------------|
| Optical cover type        | Polycarbonate bowl/cover clear |
| Optic type outdoor        | Wide street optic              |
|                           |                                |
| Operating and Electrical  |                                |
| Input Voltage             | 220 to 240 V                   |
| Line Frequency            | 50 to 60 Hz                    |
| Power Consumption         | 29 W                           |
|                           |                                |
| Temperature               |                                |
| Ambient temperature range | -25 to +35 °C                  |
|                           |                                |
| Controls and Dimming      |                                |
| Dimmable                  | Yes                            |
|                           |                                |

Datasheet, 2023, April 30 data subject to change

## CityCurve gen2

| Driver/power unit/transformer              | Power supply unit regulating with constant light |  |
|--|--|--|
|  | output   |  |
|  |  |  |
| Mechanical and Housing                     |  |  |
| Housing Material                           | Aluminum   |  |
| Optical cover material                     | Polycarbonate                                    |  |
| Mounting device                            | Spigot   |  |
|  |  |  |
| Approval and Application                   |  |  |
| Ingress protection code                    | IP65 [Dust penetration-protected, jet-proof]     |  |
| Mech. impact protection code               | IK10 [20 J vandal-resistant]                     |  |
| Protection class IEC                       | Safety class II                                  |  |
|  |  |  |
| Initial Performance (IEC Compliant)        |  |  |
| Init. Color Rendering Index Tolerance +/-2 |  |  |

| Product Data                    |                                      |
|---------------------------------|--------------------------------------|
| Order product name              | BSP295 GRN24/830 PSR-CLO WSO II 7035 |
| Full product name               | BSP295 GRN24/830 PSR-CLO WSO II 7035 |
| Full product code               | 871794312015400                      |
| Order code                      | 12015400                             |
| Material Nr. (12NC)             | 912300020016                         |
| Numerator - Quantity Per Pack   | 1                                    |
| EAN/UPC - Product/Case          | 8717943120154                        |
| Numerator - Packs per outer box | 1                                    |
| EAN/UPC - Case                  | 8717943120154                        |
|                                 |                                      |

### Dimensional drawing





