



Jargeau 400 LED

BSP641 LED52-4S/740 PSU II DS50 FG BK G1

Jargeau 400 LED, LED module 5200 lm, 740 neutral white, Safety class II, Distribution symmetrical 50, Flat glass, Black, Suspension set simple, standard

Jargeau 400 LED combines the symbolic features of the first four-sided street lamps of the 19th century with the technical performance of 21st century luminaires. It incorporates the energy-efficient LEDGINE - O engine with high-performance optics, while at the same time retaining the character of the original four-sided fixture. Designed for installation at heights of 4-6 meters, this luminaire is well suited to urban landscapes and ideal for illuminating city centers, historical areas, old villages, streets, alleys, squares and parks. Jargeau 400 LED can also enable the benefits of the latest technologies developed by Philips Lighting, including the CityTouch connected lighting system.

Product data

General Information	
Lamp family code	LED52 [LED module 5200 lm]
Light source replaceable	Yes
Number of gear units	1 unit
Driver included	Yes
Remarks	* At extreme ambient temperatures the luminaire might automatically dim down to protect components
Light source engine type	LED
Product family code	BGP641 [Jargeau 400 LED]
Lighting Technology	LED
CE mark	Yes
Warranty period	5 years

Flammability mark	-
ENEC mark	ENEC mark
EU RoHS compliant	Yes
Light Technical	
Upward light output ratio	0.03
Luminous Flux	4,111 lm
Standard tilt angle posttop	0°
Standard tilt angle side entry	-
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	108 lm/W
Color rendering index (CRI)	≥70
Light source color	740 neutral white

Jargeau 400 LED

Optical cover type	Flat glass
Luminaire light beam spread	152° x 155°
Optic type outdoor	Distribution symmetrical 50

Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Inrush current	46 A
Inrush time	250 ms
Power Consumption	38 W
Power Factor (Fraction)	0.9
Connection	Plug-in connector 2-pole Wieland/Adels compatible
Cable	-
Number of products on MCB of 16 A type B 11	

Temperature

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover material	Glass
Fixation material	Aluminum
Housing Color	Black
Mounting device	Suspension set simple, standard
Optical cover shape	Flat
Optical cover finish	Clear
Fixation diameter	Mounting device diameter 1"

Overall length	400 mm
Overall width	400 mm
Overall height	840 mm
Effective projected area	0.13 m²
Dimensions (Height x Width x Depth)	840 x 400 x 400 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK09 [10 J]
Surge Protection (Common/Differential)	4/4 kV
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.381, 0.379) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2


Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	0.5 %
-------------------------------	-------

Product Data

Order product name	BSP641 LED52-4S/740 PSU II DS50 FG BK G1
Full product name	BSP641 LED52-4S/740 PSU II DS50 FG BK G1
Full product code	871869910887800
Order code	10887800
Material Nr. (12NC)	912300023773
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699108878
Numerator - Packs per outer box	1
EAN/UPC - Case	8718699108878

Dimensional drawing



Jargeau 400 LED

