



Metronomis 1 LED

BDS580 LWFP LED50/740 II MDM TP CTGO-DG

Metronomis 1 LED Cambridge, CityTouch with future proof service, LED module 5000 lm, 740 neutral white, Safety class II, Metronomis distribution medium, Polycarbonate bowl/cover, Grey, Luminaire surge protection level until 6 kV differential mode and 8 kV common mode, Pole-mounting bracket diameter 60 mm

Our family of five, highly distinctive Metronomis 1 LED luminaires is now available in LED. The award-winning Philips Metronomis 1 LED range is designed to enhance Cambridge, Berlin, Bordeaux, Brussels, and Porto luminaires with even greater lighting performance and efficiency. Architects and lighting designers can use these luminaires and dedicated poles and brackets with a wide variety of optics. So they can create a total city lighting solution with a consistent design that still reflects differences in urban culture and history. During the day, Metronomis 1 LED integrates harmoniously with any street scene. At night, its appearance is both functional – guiding people and traffic safely through the city – and decorative, creating a pleasant ambience in city squares and pedestrian areas. The Metronomis 1 LED street lighting solution features a Philips System ready (SR) socket, making it future ready to be paired with standalone or advanced control and lighting software applications such as Interact from Signify. In addition, every Metronomis LED 1 luminaire is uniquely identifiable, thanks to the Signify Service tag app. By simply scanning a QR code, placed inside the door of the mast or directly on the luminaire, you can instantly access the configuration of the luminaire. This makes maintenance and programming operations faster and easier, and enables you to create a digital library of lighting assets and spare parts.

Product data

Metronomis 1 LED

General Information	
Lamp family code	LED50 [LED module 5000 lm]
Light source replaceable	Yes
Number of gear units	1 unit
Driver included	Yes
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value. * At extreme ambient temperatures the luminaire might automatically dim down to protect components
Light source engine type	LED
Product family code	BDS580 [Metronomis 1 LED Cambridge]
Lighting Technology	LED
Value ladder	Specification
CE mark	Yes
Warranty period	5 years
Flammability mark	-
ENEC mark	ENEC mark
EU RoHS compliant	Yes
Light Technical	
Upward light output ratio	0.03
Luminous Flux	3,850 lm
Standard tilt angle posttop	0°
Standard tilt angle side entry	-
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	122 lm/W
Color rendering index (CRI)	70
Light source color	740 neutral white
Optical cover type	Polycarbonate bowl/cover
Luminaire light beam spread	45° - 17° x 150°
Optic type outdoor	Metronomis distribution medium
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	21 A
Inrush time	0.225 ms
Power Consumption	31.5 W
Power Factor (Fraction)	0.98
Connection	Plug-in connector 5-pole Wieland/Adels compatible
Cable	-
Number of products on MCB of 16 A type B	26

Temperature	
Ambient temperature range	-40 to +50 °C
Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Control interface	GPRS network
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Grey
Mounting device	Pole-mounting bracket diameter 60 mm
Optical cover shape	Conical
Optical cover finish	Clear
Overall length	795 mm
Overall width	590 mm
Overall height	795 mm
Overall diameter	590 mm
Effective projected area	0.27 m²
Dimensions (Height x Width x Depth)	795 x 590 x 795 mm
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 8 kV common mode
Protection class IEC	Safety class II
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-7%
Initial chromaticity	(0.382, 0.378) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 100000 h	L97
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	25%
Product Data	
Order product name	BDS580 LWFP LED50/740 II MDM TP CTGO- DG

Metronomis 1 LED

Full product name	BDS580 LWFP LED50/740 II MDM TP CTGO-DG
Full product code	871869946766100
Order code	912300024030
Material Nr. (12NC)	912300024030
Numerator - Quantity Per Pack	1

EAN/UPC - Product/Case	8718699467661
Numerator - Packs per outer box	1
EAN/UPC - Case	8718699467661

Dimensional drawing

